

Truro Zoning Board of Appeals Agendaffice of Town Clerk

Remote Zoom Meeting

Monday, June 24, 2024 – 5:30 pm

www.truro-ma.gov

Received By.

Join the meeting from your computer, tablet or smartphone: https://us02web.zoom.us/j/87146819860

Dial in: +1-646-931-3860

Meeting ID: 871 4681 9860 Passcode: 673170

Open Meeting

This will be a remote public meeting. Citizens can view the meeting on Channel 8 in Truro and on the web on the "Truro TV Channel 8" button under "Helpful Links" on the homepage of the Town of Truro website (<u>www.truro-ma.gov</u>). Click on the green "Watch" button in the upper right corner of the page. Please note that there may be a slight delay (approx. 15-30 seconds) between the meeting and the television broadcast/livestream.

Citizens can join the meeting to listen and provide public comment by entering the meeting link; clicking on the agenda's highlighted link; clicking on the meeting date in the Event Calendar; or by calling in toll free. Citizens will be muted upon entering the meeting until the public comment portion of the hearing. If you are joining the meeting while watching the television broadcast/livestream, please lower or mute the volume on your computer or television during public comment so that you may be heard clearly. Citizens may also provide comment via postal mail or by emailing Liz Sturdy, Planning Department Assistant, at <u>esturdy@truro-ma.gov</u>, one week prior to the meeting; or may instead speak during the Public Comment portion of the hearing.

Public Comment Period

The Commonwealth's Open Meeting Law limits any discussion by members of the Board of an issue raised to whether that issue should be placed on a future agenda. Speakers are limited to no more than 5 minutes.

Minutes

- ♦ April 29, 2024
- ♦ May 20, 2024

Board Action/Review

♦ 2024-001/ZBA (40B) – Community Housing Resource, Inc. for property located at 22 Highland Road (Cloverleaf) (Atlas Map 36, Parcel 238; Registry of Deeds title reference Book 30796, Page 289; Plan Book 672, Page 31) located in the Seashore District. Notice of Project Change [#2], 22 Highland Road, Cloverleaf Truro Rental Housing.

Public Hearing - New

2024-004/ZBA – Amy Holt, for property located at 113 Castle Road (Atlas Map 46, Parcel 398). Applicant seeks a variance (height) or Special Permit for dwelling in the Residential District.

Board Discussion

- ♦ Hybrid Meetings
- ♦ Appointments/Reappointments attend Select Board Meeting on June 25, 2024 at 5:00 pm
 - o Staggered terms

Next Meetings Monday, July 22, 2024 at 5:30 p.m.

Adjourn

Office of Town Clerk

STAFF MEMORANDUM

To: Truro Zoning Board of Appeals

From: Barbara Carboni, Town Planner and Land Use Counsel

Date: June 19, 2024

Re: Meeting June 24, 2024

2024-004/ZBA Amy Holt (owner) and John Ferro, Pine Knoll (builder) for property located at 113 Castle Road. Applicants seek variance or special permit with respect to newly-constructed residence exceeding height limit in the Residential District.

Project History

The subject lot was created through a 2022 subdivision of an 11+ acre parcel. At the time, the lot contained a tennis court and two outbuildings. ¹ A building permit issued on August 22, 2022 for construction of a five-bedroom home. The indicated height of the dwelling was 29.2 feet. ² Construction proceeded.

Due to questions raised by an abutter regarding the finished height of the dwelling, the Building Commissioner required that the as-built height be certified by a registered engineer. The result: a height 1'6" in excess of the Zoning Bylaw maximum of 30 feet. See Narrative at p.1. By way of explanation, the applicant states that while he had identified the roof truss height as an

_

¹ One of these structures was a studio designed by Charles Zehnder. The Historical Commission reviewed the proposed demolition of the studio under the Preserving Historic Properties Bylaw. The studio was said to interfere with the intended location of the proposed residence. Through neglect, the condition of the studio had deteriorated substantially. The applicants declined to alter the location of the dwelling, or otherwise preserve the studio. The Historical Commission declined to impose a demolition delay.

²Plans indicated that the "Livable Space" of the dwelling would total 4,502 square feet. Under Zoning Bylaw 50.2.B, the Total Gross Floor Area of a residence may not exceed 3,600 sq.ft. for a minimum lot size of 33,750 sq.ft., prorated to 3,668 square feet for one acre of land "plus 300 sq. ft. for each additional contiguous acre of land, or fraction thereof prorated." See s. 50.2.B.1.a. The lot area is 3.31 acres. For the lot's first acre, 3,668 sq.ft. are allowed; the additional 2 and roughly 1/3 acres would allow for an additional 700 sq.ft. (300 + 300 + 100). The maximum Total Gross Floor Area for the lot would appear to be approximately 4,368 sq.ft. It is not clear whether the "Livable Space" of 4,368 sq.ft. is equivalent to 4,368 sq.ft. of Gross Floor Area. Total Gross Floor Area should be provided. If it exceeds 4,368 sq.ft, a special permit to exceed Total Gross Floor Area must be obtained. The Building Commissioner is reviewing this aspect of the project.

issue during design, his modification to the design (lowering the roof pitch) was not received by the truss designer. The too-tall trusses were installed, resulting in the ridge height in excess of the Bylaw maximum. See narrative at p. 1

The Building Commissioner declined to issue a certificate of occupancy and advised the applicant to seek a height variance from the ZBA. The applicant first applied for a variance, then submitted an application for a special permit.

Requested relief

The applicant states that new trusses can be designed and installed in the existing structure that will lower the ridge height by 1'9", rendering the structure conforming as to height (3" below maximum). The applicant proposes that this work be done "between the end of summer and end of year," and that the property owners be allowed to reside in the house for the summer (July, August and September) under a temporary certificate of occupancy. Narrative at p. 1. These terms are contained in a "letter of intent" filed with the application.

The applicant states that he is "not asking the board for a height variance," but rather "for the board's approval to proceed within the guidelines of the notarized letter of intent." Narrative at p. 2. In the alternative, the applicant requests a variance and states that he will abide by the letter of intent. Narrative at p. 2.

Approval of proposal for temporary occupancy permit and subsequent construction

Under the Zoning Bylaw and G.L. c. 40A, the Board has the authority to grant or deny variances; grant or deny special permits; and grant or deny appeals from orders of the Building Commissioner. The Board does not have the authority to approve (or disapprove) a proposal for occupancy of a residence under a temporary occupancy permit; or to approve (or disapprove) a construction schedule. These are functions of the Building Commissioner. Nor does the Board have authority to approve occupancy of the residence while there is a zoning violation, which is essentially what is being asked. The applicant's first request ("for the board's approval to proceed within the guidelines of the notarized letter of intent") cannot lawfully be granted.

Variance

The Board may wonder if such a thing is permissible. I would have thought not – G.L. c. 40A, s. 10 does not provide for it –but I found a handful of cases in which temporary variances were granted by boards and tolerated by the courts (or at least, not invalidated on the grounds of being temporary in nature). The Yarmouth Board of Appeals granted a variance to allow "temporary use" of a private golf course to allow public play for a period of eight years. The Milton ZBA granted a temporary variance to allow a florist to sell additional materials (e.g., Christmas trees; pumpkins) during the appropriate season. The Saugus Board of Appeals granted a temporary

³ Davenport v. Donegan, 2010 WL 8609141(Land Court, September 29, 2010)

⁴Lydon v. Town of Milton ZBA, 2012 WL 1572128 (Land Court, May 3, 2012)

variance (60 days) to allow operation of a greyhound kennel within a residential district, ⁵ and the Newton Board of Aldermen granted a temporary variance (six months) to allow a business to operate in a residential district while it found new location. ⁶ In none of these cases was the temporary nature of the variance the subject of challenge or of discussion by the court.

All of the above cases involved use variances; I found no case in which a temporary *dimensional* variance was issued. However, as compared to the applicant's primary request –the Board's approval of a plan for a temporary occupancy permit, with correction of the zoning violation to follow – a temporary height variance is at least arguably within the Board's authority to grant.

If the Board were to granta temporary height variance, it would still need to make the requisite findings under G.L. c. 40A, s. 10:

- [1] owing to circumstances relating to the soil conditions, shape, or topography of such land or structures and especially affecting such land or structures but not affecting generally the zoning district in which it is located,
- [2] a literal enforcement of the provisions of the ordinance or by-law would involve substantial hardship, financial or otherwise, to the petitioner or appellant, and
- [3] that desirable relief may be granted without substantial detriment to the public good and without nullifying or substantially derogating from the intent or purpose of such ordinance or by-law.

It's difficult to see how a structure's excess height could be pinned on the lot's soil condition, shape or topography, so the first finding would be problematic. It would also be difficult to find hardship, where case law says that construction error is not an eligible basis. See <u>DiGiovanni v. Board of Appeals of Rockport</u>, 19 Mass. App. Ct. 339 ("W]e agree that it is a misfortune that DiGiovanni has built buildings where they ought not to have been built, this is not the type of hardship that justifies a variance." In addition, where the builder has a plan for curing the height violation at no cost to the homeowner, the remaining hardship presented is that the homeowners would be unable to occupy the residence this summer. While the homeowners' situation certainly lends itself to sympathy, a finding of hardship on this basis would be a stretch, given case law.

Special Permit

Although not discussed in the narrative, the applicant has also requested a special permit in a second application form. It is unclear on what basis the Board might grant this request, as special permits are available where a *preexisting* nonconforming structure is being modified in some respect. In this case, there was no preexisting structure. Instead, a new residence *as built* violates the Bylaw height limit. The required special permit finding – that the structure is "not

⁵ Sheehan v. Board of Appeals of Saugus, 332 Mass. 188 (1955)

⁶ Colabufalo v. Public Buildings Commissioner of Newton, 336 Mass. 205 (1957)

substantially more detrimental" to the neighborhood than the existing nonconforming structure – cannot be applied to this case, and the Board would be unable to make the required finding.

De Minimis Finding

Applicant's counsel has suggested that the Board could find that the one-and-a-half-foot deviation from the Bylaw height limit of 30 feet is *de minimis* ("lacking significance or importance; so minor as to merit disregard") and accordingly that no zoning relief is required from the Board.

The Board's authority to make a "de minimis" finding is doubtful. There is no statutory or Bylaw authority for it, nor are there any standards or criteria to guide a board's decision. For this reason, any *de minimis* finding would by definition be arbitrary and/or capricious. Even if the Board does have authority to make *de minimis* findings, this is not a path I would recommend starting down—today, it's a request for one foot six inches in height; what happens when the next applicant comes in requesting a *de minimis* finding for one foot eight inches in height? Finally, even if the Board is willing to start down this path, on the merits, it is difficult to characterize a foot and a half of height in excess of the Bylaw height limit of 30 feet *de minimis*.

In short, I recommend against any *de minimis* finding1) on the grounds of dubious authority; 2) on the grounds that it will essentially invite people to build noncompliant structures and then seek *de minimis* findings from the Board; and 3) on the merits.

Other Option

As discussed above, the Board lacks authority to "approve" an arrangement by which the homeowners may occupy the residence under a temporary certificate of occupancy, or to approve occupancy of the residence while a zoning violation exists. These are matters for the Building Commissioner. It is understandable that the Building Commissioner would refer this to the Board for review, but to the extent a solution is sought to allow the homeowners to reside in the house this summer, the solution would seemingly be in the Building Commissioner's jurisdiction.⁸

A lawful solution would be for the Board to allow the applicants to withdraw the application, and for the Building Commissioner to issue a temporary occupancy permit with conditions requiring the structure to be rendered conforming by a date certain.

7

⁷ I found a single Land Court case in which the court expressly stated that the board could make a de minimis finding with respect to a three-foot deviation from a side yard setback requirement. This case was not appealed, and there are no Appeals Court or SJC cases supporting a *de minimis* finding.

⁸There is precedent for issuance and extension of a temporary certificate of occupancy while setback requirements were being cured (49 Fisher Road). In that case, the matter did come before the Board on a special permit, but a temporary occupancy permit was issued and the house was allowed to be occupied while the zoning violations continued. One of the cures for the setback violations was the redrawing of a lot line to render the structure conforming through an ANR plan. This was only recently before the Planning Board.

Board Action

22 Highland Road, Cloverleaf Truro Rental Housing: Notice of Project Change

Community Housing Resource, Inc. (CHR), developer and permittee for the Cloverleaf project, has submitted a second request for modification of the comprehensive permit originally granted by the Board on January 14, 2021. In the original decision, the Board approved a 39-unit residential project on Town-owned land off Highland Road, on the east side of Route 6. In its first request for modification of the permit, heard by the Board on January 22, 2024, CHR sought approval, as "insubstantial changes," modifications to the project includingan increase in units from 39 to 43; combination of the two northernmost buildings (two units each) into a single seven-unit building including three of the new units; the addition of a unit to the apartment building (Building 21) and resulting reduction in community space in that building; the addition of four parking spaces; and an alteration of the unit mix (affordability levels);. The Board approved these changes as "insubstantial" and an amended permit issued.

As discussed below, CHR's second request for modification seeks 1) to amend Condition 19 (unit mix); 2) to combine four 2-unit structures into two four-unit structures; 3) to alter previous grading plans, the effect of which on the height of buildings 1-3-5-7 and 2-4-6-8 needs to be explained by the applicant; and 4) additional grading, parking, landscape and planting plans.

Initial Determination: Substantial or Insubstantial Change

Because the project was permitted under G.L. c 40B and associated regulations, there is a particular process for modifications to the project. Under 760 CMR 56.05(11)("Changes after Issuance of a Permit"), a permittee seeking to alter an approved project "shall promptly notify the Board in writing, describing such change." 760 CMR 56.05(11)(a); hence the title of CHR's application, "Notice of Project Change." **The ZBA's initial determination, to be made within 20 days of submission of the Notice** is whether the proposed change to the project is "substantial" or "insubstantial," based on factors set out elsewhere in the regulations (discussed below).

If the Board determines that the change is "insubstantial," the comprehensive permit "shall be deemed modified to incorporate the Change." 760 CMR 56.05(b). No public hearing takes place, and no further action is taken by the Board. If the Board determines that the change is "substantial," the Board holds a public hearing, opened within 30 days of such determination. Only the proposed changes "or aspects of the Project affected thereby" are at issue in the hearing. 760 CMR 56.05(c). Hearing procedures follow the same rules as for a board's initial hearing of a comprehensive permit: 180 days to conduct the hearing; 40 days thereafter to issue a decision. If the Board fails to make the substantial/insubstantial change determination within 20 days of the Notice of Project Change,

_

⁹ This Notice of Project Change was submitted on June 17, 2024; the Board must act by July 6, 2024.

the comprehensive permit is deemed modified to incorporate the changes. 760 CMR 56.05(11)(b).

Standard for Determining "Insubstantial" or "Substantial" Change

760 CMR 56.07(4) provides guidance for the insubstantial/substantial determination the Board must make with respect to the Notice of Project Change:

- "(c) The following matters generally will be substantial changes:
 - 1. An increase of more than 10% in the height of the building(s);
 - 2. An increase of more than 10% in the number of housing units proposed;
 - 3. A reduction in the size of the site of more than 10% in excess of any decrease in the number of housing units proposed;
 - 4. A change in building type (e.g., garden apartments, townhouses high-rises); or
 - 5. A change from one form of housing tenure to another.
- (d) The following matters generally will not be substantial changes:
 - 1. A reduction in the number of housing units proposed;
 - 2. A decrease of less than 10% in the floor area of individual units;
 - 3. A change in the number of bedrooms within individual units, if such changes do not alter the overall bedroom count of the proposed housing by more than 10%
 - 4. A change in the color or style of materials used; or
 - 5. A change in the financing program under which the Applicant plans to receive a Subsidy, if the change affects no other aspect of the proposal."

760 CMR 56.07(4).

Project Changes

<u>Unit Mix (affordability)</u>. As the Board will remember, in January, at the Applicant's request, the permit was amended to increase the number of units from 39 to 43, and unit mix changed to include more units at lower affordability levels, reflecting requirements of the project's subsidy (Low Income Housing Tax Credit program). These changes are illustrated in the following charts:

Original Permit

| Income Tiers | |
|--------------|----|
| 30% AMI | 5 |
| 80% AMI | 15 |
| 80%-120% | 8 |
| Market | 6 |
| TBD | 5 |
| Total | 39 |

Amended Permit

| Income Tiers | |
|--------------|----|
| 30% AMI | 6 |
| 80% AMI | 25 |
| 80%-100% AMI | 4 |
| Market | 4 |
| TBD | 4 |
| Total | 43 |

In the current application, the Applicant seeks further revisions of Condition 19 in the Amended permit, which contains the unit mix. ¹⁰ As the Applicant explains, these changes are needed to obtain additional subsidies to make the project "economic."

Current Request for Amendment

| Income Tiers | |
|--|----|
| 30% AMI | 6 |
| 60% or 80% AMI(but most units restricted | 29 |
| to 60%) | |
| 80%-100% AMI | 4 |
| Market | 4 |
| Total | 43 |

The specific language requested by the Applicant to replace the current Condition 19 is:

"Of the forty-three units, six (6) will be affordable to individuals/households earning up to 30% of the Area Median Income (AMI); twenty-nine (29) will be affordable to individuals/households earning up to 80% AMI, but most of this category will be limited to individuals/households earning up to 60% AMI at initial occupancy; four (4) will be affordable to individuals earning from 80 to 100% AMI; four (4) will be market rate units. However, the foregoing distribution is subject to the approval of the Subsidizing Agency and may be changed in accordance with the requirements of the subsidizing agency without further approval from the Board."

See Ex.4a.2. The most significant changes to the Amended Decision are:

• the largest number of units (now 29, including the 4 "TBD") will, instead of being available to households earning up to 80% AMI, be available mostly to households earning up to 60% AMI.¹¹

1

¹⁰ Exhibit 4a of the Applicant's packet cites the unit mix condition in the original comprehensive permit, butit is the Amended Permit, not the original permit, that is being modified.

¹¹ Proposed Condition 19 states that most of this category "will be limited to individuals/ households earning up to 60% AMI *at initial occupancy*" (emphasis added). The applicant might be asked at the meeting what this means for occupancy subsequent to the initial occupancy.

• the addition of language providing that the Board's approval is not required for further changes to the unit mix required by the subsidizing agency.

As explained by the Applicant, the flexibility provided by this language - and specifically, the ability to change the unit mix without Board approval - is needed to satisfy subsidizing agency requirements, and to allow the project to be eligible for desired funding. The Applicant may explain this further at the meeting. 12

If the Board is inclined to grant this application as an "insubstantial change," it could incorporate the applicant's suggested language into its Second Amended Decision. In the alternative, it could substitute the following proposed language for the second ("However. . . .) sentence:

"However, the foregoing distribution is subject to the approval of the Subsidizing Agency and may be changed in accordance with the requirements of the subsidizing agency. Such further changes do not require the approval of the Board, but the Applicant shall inform the Board of any revisions to the distribution."

I believe this would preserve the Applicant's intent.

Combination of Units/Buildings.

In the plans originally approved by the Board, there were two duplexes on either side of the project driveway, closest to Highland Road. As proposed, the duplexes on each side have been combined into four-unit buildings. See Buildings 1-7 and 2-8, "Cloverleaf Truro Rental Housing, Notice of Project Change - #2" dated June 17, 2024. The number of buildings in the project as redesigned is 10.

The Applicant has proposed language modifying Condition 18 of the original permit to reflect these changes. I find the proposed language confusing. The Board could adopt the Applicant's language, or in the alternative, the following:

"Buildings 1-3 and 5-7 are combined into a single building, Building 1-7. Buildings 2-4 and 6-8 are combined into a single building, Building 2-8. The total number of buildings comprising the project is ten (10). Condition 18 of the original permit, and Condition 3 of the Amended Permit are modified accordingly."

Grade change/potential building height changes:

The Applicant's Narrative Regarding Other Considerations (Ex. 4c.2) states that

"The Building Height as measured for existing grade has been recalculated based on the existing grade elevations at the proposed corners of the combined building 1-3-5-7 and 2- 4-6-8. There is no change to the building height as previously proposed."

¹² In any context but a 40B project, allowing the project to change without further approval by the Board would make no sense. However, the 40B world is different; the regulations and case law give substantial powers to the subsidizing agency and constrains municipal authority.

The plan set in the application includes elevations of Building 1-7 and 2-8, but the height of these buildings is not indicated.

The Notice of Project Change also includes charts pertaining to grade and building height, existing and proposed, for Buildings 1-7 and 2-8. These indicate decreases in average grade (from existing to proposed), and increases in building height above average grade (from existing to proposed. The Applicant or project engineer may be asked to explain the grade changes and their effect on the height of these buildings. If the resulting height of either building exceeds the Bylaw maximum of 30 feet, a waiver by the Board would be required. The specific finished height of the building(s) and the specific waiver in feet/inches should be indicated.

Grading, Parking, Landscaping and Planting Plans

The submitted site plan and plan set indicate revised grading, parking, landscaping and planting plans (see, in particular sheets L2.01-L4.01), and modifications to The Narrative Regarding Other Considerations notes that the revised plans include trash and bicycle storage; EV charging locations, and outdoor exercise equipment. The Applicant could be asked to identify the particulars.

Application of standard to Notice of Project Change

The Notice of Project Change includes one change identified in the regulations as "generally... [a] substantial change": four of the buildings, duplexes, are being replaced by two four-unit (multi-family) buildings. This is a "change in building type" identified as a substantial change. See 760 CMR 56.07(4)(c)(4).

However, the regulation states that the listed changes are *generally* substantial, leaving the Board some discretion in making its determination of substantial/insubstantial change. That is, the Board is not required to find that the project change is substantial simply because there is a change in building type.

If it is determined that there is an increase in the height of Building 1-7 or 2-6, and if so whether there is "[a]n increase of more than 10% in the height of the building(s)," the Board would again have discretion in making its determination of substantial/insubstantial change. See 760 CMR 56.07(4)(c)(1).

Finally, in determining whether the project change is substantial or insubstantial, the Board should consider the proposed changes in the context of the project *as a whole*- that is, consider what is not changing, as well as what is.

* TOPPORATED

TOWN OF TRURO

ZONING BOARD OF APPEALS

Meeting Minutes
April 29, 2024 – 5:30 pm
REMOTE ZONING BOARD OF APPEALS MEETING

Members Present (Quorum): Chris Lucy (Chair); Darrell Shedd (Vice Chair); Dave Crocker; Art Hultin

Members Absent: Nancy Medoff; Russ Braun (Alt.)

Other Participants: Barbara Carboni – Town Planner/Land Use Counsel

Remote meeting convened at 5:42 pm, Monday, April 29, 2024, by Chair Lucy. Town Planner/Land Use Counsel Carboni announced that this was a remote meeting.

<u>Public Comment Period:</u> There were no public comments made.

Minutes: None

Public Hearings (Continued)

2022-017/ZBA (VAR/SP) - Ebb Tide on the Bay Condominiums for property located at 538 Shore Road (Atlas Map 7, Parcel 7, Registry of Deeds title reference: Book 5671, Page 232). Applicant seeks a Special Permit under M.G.L. Ch. 40A §6 and §30.7.A of the Truro Zoning Bylaw for the relocation of three non-conforming structures on a lot in the Beach Point Limited Business District.

Chair Lucy announced that there was a request to continue this matter to May 20, 2024, at 5:30 pm as today is a religious holiday.

Vice Chair Shedd made a motion to continue the matter of 2022-017/ZBA (VAR/SP) to May 20, 2024 at 5:30 pm.

Member Crocker seconded the motion.

ROLL CALL VOTE:

Vice Chair Shedd – Aye

Member Crocker - Aye

Member Hultin – Aye

Chair Lucy - Aye

So voted, 4-0-0, motion carries.

Vice Chair Shedd made a motion to adjourn at 5:45 pm.

Member Crocker seconded the motion.

ROLL CALL VOTE:

Vice Chair Shedd - Aye

Member Crocker – Aye

Member Hultin - Aye

Chair Lucy - Aye

So voted, 4-0-0, motion carries.

Respectfully submitted,

Alexander O. Powers, Board/Committee/Commission Support Staff



TOWN OF TRURO

ZONING BOARD OF APPEALS

Meeting Minutes

May 20, 2024 – 5:30 pm

REMOTE ZONING BOARD OF APPEALS MEETING

<u>Members Present (Quorum)</u>: Chris Lucy (Chair); Darrell Shedd (Vice Chair); Nancy Medoff; Dave Crocker; Art Hultin, Russ Braun (Alt.)

Members Absent:

Other Participants: Ben Zehnder (Attorney for Crow's Nest Condominium Trust – Applicant); Christopher Agostino (Attorney and Representative for Abutters of Crow's Nest Condominium Trust); Christopher J. Snow (Attorney and Applicant for 538 Shore Road and Ebb Tide); Sally McSween (Representative for Condominium Association); Ben Zehnder (Attorney and Representative for Abutters: Marie Belding and Pat Callinan); Marie Belding (Abutter); Pat Callinan (Abutter); Elaine Brigman (Ebb Tide Resident); Clem Berrio (Ebb Tide Resident)

Remote meeting convened at 5:30 pm, Monday, May 20, 2024, by Chair Lucy. Chair Lucy announced that this was a remote meeting which is being broadcast live on Truro TV Channel 8 and is being recorded. Chair Lucy introduced the Members of the ZBA.

Public Comment Period

Chair Lucy invited any individual who wished to comment and there were no public comments made.

Public Hearing (Continued)

2024-002/ZBA - Jennifer Cabral (Nearen & Cubberly Nominee Trust, Christopher Snow, Trustee), for property located at 491 Shore Road (Atlas Map 7, Parcel 4, Registry of Deeds Book 8309 and Page 131). Applicant seeks a special permit or variance for alteration/reconstruction of pre-existing nonconforming use/structure in the Beach Point Limited Business District.

Chair Lucy announced that this was a matter that had previously been decided by the ZBA and that the Attorneys representing the Applicant and Abutters had requested that the matter be reopened as they have jointly asked that additional proposed conditions be considered in the granting of the permit.

Attorney Zehnder provided background information. Attorney Zehnder noted that Attorney Agostino had called him recently and that not all the Abutters agreed with the new additional proposed conditions. Attorney Zehnder then requested that the Planning Board render a decision this evening in favor of the Applicant's application.

Attorney Agostino concurred that some of the Abutters did not agree with the additional requested conditions.

Since the proposed conditions were not agreed upon, Chair Lucy opined that the hearing should close and the previous decision should stand.

Note: Only the 5 full Members would vote on this matter.

Chair Lucy made a motion to close the hearing in the matter of 2022-017/ZBA (VAR/SP) and to allow the ZBA's previous decision to stand.

Vice Chair Shedd seconded the motion.

ROLL CALL VOTE:

Member Medoff – Aye

Member Crocker - Aye

Vice Chair Shedd - Aye

Member Hultin - Aye

Chair Lucy - Aye

So voted, 5-0-0, motion carries.

2022-017/ZBA (VAR/SP) - Ebb Tide on the Bay Condominiums for property located at 53 8 Shore Road (Atlas Map 7, Parcel 7, Registry of Deeds title reference: Book 5671, Page 232). Applicant seeks a Special Permit under M.G.L. Ch. 40A §6 and §30.7.A of the Truro Zoning Bylaw for the relocation of three non-conforming structures on a lot in the Beach Point Limited Business District.

Chair Lucy said that this matter had been continued and the Members had new information contained in their packets this evening. Chair Lucy noted that his requested parking plan was not included in tonight's packet.

Attorney Snow joined the hearing by telephone and said that the parking plan had been submitted to Town Planner/Land Use Counsel Barbara Carboni and Planning Department Assistant Liz Sturdy last Thursday. Attorney Snow was unsure why the parking plan was not included in tonight's packet, and he then provided a summarized update to the Members. *Note: the parking plan was later discovered in the Members' packet*.

Chair Lucy, the Members, Attorney Zehnder and Attorney Snow discussed the following highlighted topics: the parking plan; unit designations and parking spaces which are dedicated to those units; the concerns regarding the increased size and height of the proposed buildings; the possibility of the Members not approving this proposed project and the consequences affecting the neighborhood and the shoreline; the issues of septic systems and groundwater; the cost of \$200,000 in permitting fees over the last five years incurred by the Applicant and the potential cost of an appeal to the Truro taxpayers; and the straw poll of the Members taken this evening that reflected a 3-2 opposition to the proposed project.

Chair Lucy then invited the members of the public to comment on this matter and Chair Lucy recognized the following individuals: Ms. McSween, Ms. Belding, Ms. Callinan, Ms. Brigman, Mr. Berrio, and Attorney Snow.

At the request by Attorney Snow for a continuance of 45 days to give time for the new architect on the project to address the concerns expressed by the Members and potentially submit new drawings to

appease those concerns before a final vote would be taken. Chair Lucy noted that an approved request for a continuance would be a continuance to July 22, 2024.

Chair Lucy and the other Members who were in opposition to the proposed project then briefly clarified their comments so the new architect could develop plans which would better address their concerns.

Note: Only the 5 full Members would vote on this matter.

Vice Chair Shedd made a motion to continue the matter of 2022-017/ZBA (VAR/SP) to July 22, 2024. Member Medoff seconded the motion.

ROLL CALL VOTE:

Member Crocker - Aye

Vice Chair Shedd - Aye

Member Medoff – Aye

Member Hultin – Aye

Chair Lucy – Aye

So voted, 5-0-0, motion carries.

Minutes

Chair Lucy led the review of the minutes of February 26, 2024 for edits or corrections and there were none.

Vice Chair Shedd made a motion to approve the minutes of February 26, 2024 as written.

Member Crocker seconded the motion.

ROLL CALL VOTE:

Member Crocker - Aye

Vice Chair Shedd - Aye

Member Medoff – Aye

Member Hultin – Aye

Member Braun - Aye

Chair Lucy - Aye

So voted, 6-0-0, motion carries.

Chair Lucy led the review of the minutes of March 25, 2024 for edits or corrections and there were none. Vice Chair Shedd will not vote on these minutes as he was not present at the meeting.

Member Hultin made a motion to adjourn at 5:45 pm.

Member Braun seconded the motion.

ROLL CALL VOTE:

Member Braun - Aye

Member Crocker - Aye

Member Medoff – Aye

Member Hultin – Aye

Chair Lucy - Aye

So voted, 5-0-0, motion carries.

Board Discussion

Chair Lucy led the discussion, as requested by Member Hultin, regarding hybrid ZBA meetings. The Members were supportive to start hybrid meetings like the Select Board but agreed that this topic should be discussed further with input from Town Planner/Land Use Counsel Carboni.

Chair Lucy led the discussion on upcoming appointments/reappointments. Chair Lucy reminded the Members that if they are up for reappointment, they have to reapply should they wish to continue serving on the ZBA. Five current Members are up for reappointment by June 30, 2024. Member Braun said that he had reapplied. Chair Lucy also noted that ZBA Alternate Member Joe McKinnon had moved to Florida but had not resigned from the ZBA.

Chair Lucy announced that the next meeting was scheduled for Monday, June 24, 2024, at 5:30 pm. Member Medoff asked if the communication had been distributed by the Planning Department to applicants regarding timelines and deadlines for the submission of documents.

Chair Lucy also said that the Planning Board will meet tomorrow evening to discuss the priorities for the next year and if anyone has any ideas to submit them to the Planning Board.

Member Medoff made a motion to adjourn at 6:58 pm.

Vice Chair Shedd seconded the motion.

ROLL CALL VOTE:

Member Braun – Aye

Member Crocker - Aye

Vice Chair Shedd - Aye

Member Medoff - Ave

Member Hultin - Aye

Chair Lucy - Aye

So voted, 6-0-0, motion carries.

Respectfully submitted,

Alexander O. Powers

Board/Committee/Commission Support Staff



FREEMAN LAW GROUP LLC

Attorneys at Law

Peter L. Freeman pfreeman@freemanlawgroup.com Tel (508) 362-4700 || Mobile (781) 854-2430 Nancy J. MacPhee Legal Assistant nmacphee@freemanlawgroup.com Tel. (508) 362-4700 ext 3

June 17, 2024

Christopher Lucy, Chairman Town of Truro Zoning Board of Appeals Truro Town Hall 24 Town Hall Road P.O. Box 2030 Truro, MA 02666

Re: 22 Highland Road / Cloverleaf Truro Rental Housing Comprehensive Permit Case Reference: 2019-008/ZBA

NOTICE OF PROJECT CHANGE

Dear Mr. Lucy:

Reference is made to the above-described Comprehensive Permit issued to my client Community Housing Resource, Inc. by Decision of the Board voted on or about February 3, 2021 (the "Comprehensive Permit").

On behalf of my clients, this letter is requesting that the Board approve: 1) clarification of changes to the affordability mix for the Project as previously modified by a Notice of Project Change Decision dated January 22, 2024; 2) reducing the number of buildings on the site from 12 to 10 by joining two duplex structures into four unit structures, and 3) modifications to the site plan as most recently approved by the aforesaid Notice of Project change decision specifically adjusting grading to accommodate joined buildings and parking locations; all as described below.

1. Affordability Mix.

Change Condition 19 of the Comprehensive Permit to read as follows:

The unit mix (of affordability levels) is modified to the following: Of the forty-three units, six (6) will be affordable to individuals/households earning up to 30% of the Area Median Income (AMI); twenty-nine (29) will be affordable to individuals/households earning up to 80% AMI, but most of this category will be limited to individuals/households earning up to 60% AMI at initial occupancy; four (4) will be affordable to individuals/households earning from 80 to 100% AMI; four (4) will be market rate units. However, the foregoing distribution is subject to the approval of the Subsidizing Agency and may be changed in accordance with the requirements of the Subsidizing Agency without further approval from the Board.

- 2. Site Plan. The proposed modifications are shown on the revised Site Plan submitted herewith prepared by J. M. O'Reilly & Associates, Inc. dated June 14, 2024 Including: a) joining of duplex buildings 1-3 and 5-7 to create a single building 1-3-5-7 with the same unit / bedroom mix; b) joining of duplex buildings 2-4 and 6-8 to create a single building 2-4-6-8 with the same unit / bedroom mix, together with required adjustment to grading and parking configuration; and, c) relocation of the emergency access egress gate to accommodate new outdoor exercise equipment.
- **3. Landscape and Planting Plan**. The Landscape and Planting Plan has been further developed as construction drawings. This plan incorporates refinements of grading at parking areas, planting placement with the same plant list originally presented, The Landscape and Planting Plan also incorporates locations of trash and bicycle storage, EV parking, and the outdoor exercise equipment.

These modifications are necessitated by a substantial increase in the cost of construction since the time the Comprehensive Permit was issued, and a need to satisfy the requirements of Commonwealth of Massachusetts Executive Office of Housing and Livable Communities under the Low Income Housing Tax Credit Program as to financial feasibility.

This Notice of Project Change is provided pursuant to the provisions of 760 CMR 56.05(11)(a), and I request that the Board determine that the proposed changes are insubstantial, in accordance with 760 CMR 56.05(11)(a) and (b) and 760 CMR 56.07(4). As you know, pursuant to these regulations, the Board is required to determine within twenty (20) days whether the changes are insubstantial; if it is determined that they are insubstantial or if notice is not provided by the Board to the contrary within such twenty (20) day period, the Comprehensive Permit shall be deemed modified to incorporate the changes. The above process does not require a public hearing. A public hearing is only required if the Board determines that the changes are substantial changes. The public hearing must be within thirty (30) days of a timely determination that the changes are substantial.

In the Chapter 40B Regulations, as described in 760 CMR 56.07(4), there are guidelines indicating that requested modifications are generally considered insubstantial if they do not change the type of housing tenure (in our case, the project will still be rental housing), and if they do not increase or decrease the number of units by more than ten (10%) percent.

We request that this matter be placed on your Agenda for your regular monthly meeting of June 24, 2024.

Thank you.

Very truly yours,

Peter L. Freeman

Peter Freeman

Enc.

cc: Ted Malone Barbara Carboni

EXHIBIT 4a.2

Notice of Project Change 2 Cloverleaf Truro Rental Housing Narrative Unit Mix Affordability comparison to ZBA Decision

The ZBA Decision approving the Comprehensive Permit under Terms and Conditions, Paragraphs 18 and 19 states:

- "18. The project shall consist of thirty-nine units, twenty-four of which shall be contained in twelve two-family buildings and fifteen of which shall be contained in a three-story apartment building (also containing community and office space) constructed in conformity with the Plans specified in condition 3 above.
- 19. No fewer than twenty (20) of the Project units constructed and rented shall be affordable, in perpetuity, to individuals and / or families earning no more than 80% of Area Median Income (AMI) as calculated pursuant to formulas determined by the U.S, Department of Housing and Urban Development (HUD) or DHCD. Of these twenty units, five will be affordable to households earning no more than 30% of AMI, and fifteen will be affordable to households earning no more than 80% AMI. Eight units will be affordable to earning between 80% and 120% AMI. Six units will be unrestricted / market rate. The remaining five units will be allocated as warranted by funding sources."

As needed to satisfy funding sources, "remaining five units" were also allocated to the "no more than 80% of Area Median Income (AMI)" for a total of 25 in that income tier.

With significant increases in construction costs, higher interest rates and higher premiums for insurance coverage, the financial feasibility of the Cloverleaf development has been impacted and has become "uneconomic". The additional subsidy resources that are potentially available are targeted to the lower income tiers 30% AMI / 60% AMI and 80% AMI. As approved by the ZBA in previous Notice of Project Change, Unit Affordability Mix was modified as follows: two of the six unrestricted / market rate units will need to be shifted to the "no more than 80% of Area Median Income (AMI)"; and, up to four of the eight 80% to 120% AMI units will may need to be shifted to the "no more than 80% of Area Median Income (AMI)", and, each of the four additional units to be created pursuant to this Notice of Project Change, will be designated "no more than 80% of Area Median Income (AMI)".

Since the funding sources further restrict eligibility to 60% AMI at initial occupancy, therefore, Terms and Conditions, Paragraph 19 should be clarified / modified in the decision as follow:

"19. Of the forty-three units, six (6) will be affordable to individuals/households earning up to 30% of the Area Median Income (AMI); twenty-nine (29) will be affordable to individuals/households earning up to 80% AMI, but most of this category will be limited to individuals/households earning up to 60% AMI at initial occupancy; four (4) will be affordable to individuals/households earning from 80 to 100% AMI; four (4) will be market rate units. However, the foregoing distribution is subject to the approval of the Subsidizing Agency and may be changed in accordance with the requirements of the Subsidizing Agency without further approval from the Board.

EXHIBIT 4c.2

Notice of Project Change 2 Cloverleaf Truro Rental Housing Narrative regarding Other considerations

Number of Bedrooms and Title 5 Design Flow

The number of bedrooms in the Cloverleaf Development is unchanged at 68 bedrooms. Wastewater Treatment System Design is unchanged.

Storm Water Drainage

Storm Water Drainage Systems for the development are not impacted by the changes proposed.

Number of Buildings on the Lot

The number of Buildings on the lot has decreased from the 13 in the original approved plan, to 12 as approved as part of the NoPC /insubstantial change. To achieve more efficiency in construction costs and energy consumption, Buildings 1-3 and 5-7 have been combined into one Building 1-3-5-7; and, Buildings 2-4 and 6-8 have been combined into another Building 2-4-6-8. Together this reduces the number of buildings on the lot to 10.

Building Lot Coverage

The area (square footage) of the building foot print (lot coverage) of the combined buildings 1-3 and 5-7, and 2-4 and 6-8 remains the same.

Building Height

The Building Height as measured for existing grade has been recalculated based on the existing grade elevations at the proposed corners of the combined building 1-3-5-7 and 2-4-6-8. There is no change to the building height as previously proposed.

Parking and Paved Area Lot Coverage


Four additional parking spaces are provided to support the four additional units. Two of those parking spaces are accommodated on previously paved areas so only two spaces are increasing lot coverage approximate 400 square feet. The number of parking space provided remains at 87, however, the location of the parking spaces and sidewalks at building 21 and 22 and at Building 1-3-5-7 and 2-4-6-8 have been adjusted slightly on the lot to accommodate necessary grading adjustments in coordination with the Landscape Architect. Shared EV Charging Locations and Outdoor Exercise Equipment have also been added as required for Enterprise Green Communities Certification.


Landscape Plan and Planting Plan

The Landscape and Planting Plan submitted originally has been updated with the Landscape Architect brought to the Design Team. This plan also incorporates trash and bicycle storage for townhouses and fourplex units.

| Cloverleaf Truro Rental Housing - Building 1-3-5-7 - Average Grade | | | |
|--|-------|--|--|
| | | | |
| Average Existing Grade | 49.3' | | |
| Average Proposed Grade | 44.3' | | |
| Building Height Above Average Existing Grade | 32.0' | | |
| Building Height Above Average Proposed Grade | 37.0' | | |

| Cloverleaf Truro Rental Housing - Building 2-4-6-8 - Average Grade | | |
|--|-------|--|
| | | |
| Average Existing Grade | 49.3' | |
| Average Proposed Grade | 47.1' | |
| Building Height Above Average Existing Grade | 33.8' | |
| Building Height Above Average Proposed Grade | 36.0' | |





GRADING NOTES

- The Landscape Contractor shall verify location(s) of and protect all utilities, drainage, and sub—surface drainage structures. Call DIG SAFE (888.344.7233).
- 3. DISCLAIMER: Fine grading by CBA Landscape Architects is based on overall site grading provided by Civil Engineer; see Civil drawings. Running slopes exceeding 5% have been included in these plans as directed by the Client and Civil Engineer. All code and regulatory compliance for this project is by Others.
- 4. Grade stakes to be set for approval by Landscape Architect prior to installation of gravel bases and prior to installation of all paving, edges, walls, and furniture.
- 5. All transitions to existing grades to be smooth and gradual, with 1.8% maximum cross—slopes on all paths.
- Contractor shall notify Landscape Architect if any proposed conditions exceed 1.8% cross—slope once subbase materials are installed and prior to installing finish material.
- 7. Verify existing grades in field. Notify Civil Engineer and Landscape Architect of any discrepancies or conflicts.
- 8. Any area outside the Limit of Work Line which is disturbed shall be restored to previous conditions at no cost to the Owner.
- 9. Contractor shall clean all drainage basins within the area of construction of silt, soil, and debris prior to and at the conclusion of construction.

LEGEND


Property Line

Existing Contour

Proposed Contour


16.26 Proposed Spot Grade

FOR OVERALL GRADING,
SITE DRAINAGE
INFRASTRUCTURE, AND
UTILITY NOTES, SEE CIVIL
PLANS



AMENTA EMMA

ARCHITECTS




ARCHITECTS

CLOVERLEAF - TRURO

CBA Landscape Architects LLC

24 THORNDIKE STREET | CAMBRIDGE MA 02141






PROJECT DATA

CONSTRUCTION DOCUMENTS

FINE GRADING PLAN **ENLARGEMENT 2**

PLANTING NOTES

- 1. The Contractor shall protect all utilities prior to starting construction.
- 2. The Contractor shall supply all plant materials in quantities sufficient to complete all planting shown on this drawing.
- 3. All plant materials to conform to guidelines established by the American Standard for Nursery Stock published by the American Assn. of Nurserymen.
- 4. All plant materials to be selected by the Landscape Architect at the nursery unless otherwise directed by the Landscape Architect.
- 5. All plants to be located on the site for approval of the Landscape Architect prior to installation.
- 6. If the Plant List does not agree with the Planting Plan, the Plan shall be followed.
- 7. The Contractor shall guarantee all plant materials for one year following approved
- 8. No trees are to be planted before the rough grades have been accepted by the Landscape Architect.
- 9. All landscaped areas disturbed by construction inside and outside the Limit of Work are to



AMENTA EMMA ARCHITECTS

CHR

- 4 QV .


CLOVERLEAF - TRURO

22 HIGHLAND ROAD TRURO, MA.

CONSULTANTS

CBA Landscape Architects LLC

landscape architecture urban design master planning



PROJECT DATA

PROJECT NUMBER CHECKED FILE REFERENCE M:\0-CBA-Cad\Multifamily\Cloverleaf Truro with TCB

HISTORY OF SUBMISSIONS

CONSTRUCTION **DOCUMENTS**

SHEET TITLE


PLANTING PLAN **ENLARGEMENT 1**


<u>PLANT LIST</u>

| <u> </u> | • • | | | |
|----------------|------------|--------------------------------|-----------------------|--------------|
| DECIDUC | US TR | EES | | |
| SYM | QTY | | COMMON NAME | SIZE |
| AC | 11 | Amelanchier canadensis | Serviceberry | 7-8' Ht. B&B |
| | | | | multistem |
| FG | 1 | Fagus grandifolia | American Beech | 3-3.5" Cal. |
| NS | 1 | Nyssa sylvatica | Black tupelo—sour gum | 3-3.5" Cal. |
| QA | 6 | Quercus alba | White Oak | 3-3.5" Cal. |
| QC | 8 | Quercus coccinea | Scarlet Oak | 3-3.5" Cal. |
| QR | 2 | Querucs rubra | Northern Red Oak | 3-3.5" Cal. |
| QV | 4 | Quercus velutina | Eastern Black Oak | 3-3.5" Cal. |
| | | | | |
| <u>EVERGRE</u> | | | 00141011 114145 | CIZE |
| SYM | QTY_ | BOTANICAL NAME | COMMON NAME | SIZE |
| IO "V | 6 | llex opaca | American Holly | 7-8' Ht. B&B |
| JV ". Œ | 10 | Juniperus virginiana | Eastern Red Cedar | 7-8' Ht. B&B |
| JVT | 36 | Juniperus virginiana | Eastern Red Cedar | 5-6' Ht. B&B |
| CHEHEO | | 'Taylor" | 'Taylor' | |
| SHRUBS SYM | | DOTANICAL NAME | COMMON NAME | CIZE |
| <u>SYM</u> | QTY | BOTANICAL NAME | COMMON NAME | SIZE |
| CA | 82 | Clethra alnifolia '16 candles' | Dwarf Summersweet | 18-24" HxW |
| GB | 177 | Gaylussacia baccata | Black Huckleberry | 18-24" HxW |
| MP | 52 | Morella pensylvanica | Northern Bayberry | 24-30" HxW |
| VD | 15 | Vibernum dentatum | Arrowwood Viburnum | 24-30" HxW |
| AU | 16 | Arctostaphylos uva—ursi | Bearberry | 24-30" HxW |
| | | , , | · | |
| <u>VINES</u> | | | | |
| SYM | <u>QTY</u> | BOTANICAL NAME | COMMON NAME | SIZE |
| CLV | 15/ | Clomatic virginians | Woodbine Vine | 2 Ot not |
| CLV | | Clematis virginiana | Woodbine vine | 2 Qt. pot |


Virginia Creeper Vine 2 Qt. pot

82 Parthenocissus quinquifolia











NOTE:
1. New shrub beds to have a minimum of one foot planting soil.





AMENTA EMMA

ARCHITECTS

CHR

CLOVERLEAF - TRURO

22 HIGHLAND ROAD TRURO, MA.

CONSULTANTS

CBA Landscape Architects LLC

24 THORNDIKE STREET | CAMBRIDGE MA 02141 phone 617.945.9760 | www.cbaland.com | cba@cbaland.com landscape architecture urban design master planning

17-19 13-15 9-11




PROJECT DATA PROJECT NUMBER CURRENT SUBMISSION DATE 05.22.2024 CHECKED SCALE 1" = 20'-0" FILE REFERENCE M:\0-CBA-Cad\Multifamily\Cloverleaf Truro with TCB

HISTORY OF SUBMISSIONS

CONSTRUCTION DOCUMENTS

SHEET TITLE

LANDSCAPE DETAILS





A-1.0 - BUILDINGS 2-4-6-8 - LOWER LEVEL


3/16" = 1'-0"

CLOVERLEAF | 06/17/2024

AMENTA EMMA











BLDG 2-4-6-8 - EAST ELEVATION

SCALE: 1/8" = 1'-0"

2 BLDG 2-4-6-8 - NORTH ELEVATION SCALE: 1/8" = 1'-0"

A-2.1 - BUILDING 2-4-6-8 - ELEVATIONS

1/8" = 1'-0"

AMENTA|EMMA




1 BLDG 2-4-6-8 - WEST ELEVATION SCALE: 1/8" = 1'-0"

2 BLDG 2-4-6-8 - SOUTH ELEVATION SCALE: 1/8" = 1'-0"

A-2.2 - BUILDING 2-4-6-8 - ELEVATIONS


1/8" = 1'-0"


AMENTA|EMMA




CLOVERLEAF | 06/17/2024

AMENTA|EMMA









2 1-3-5-7 - SOUTH ELEVATION SCALE: 1/8" = 1'-0"

1-3-5-7 - EAST ELEVATION

SCALE: 1/8" = 1'-0"

B-2.1 - BUILDING 1-3-5-7 - ELEVATIONS

1/8" = 1'-0"

CLOVERLEAF | 06/17/2024

AMENTA EMMA



2-4-6-8 - NORTH ELEVATION

SCALE: 1/8" = 1'-0"

 $2^{\frac{2-4-6-8-\text{WEST ELEVATION}}{\text{SCALE: }1/8"=1'-0"}}$

B-2.2 - BUILDING 1-3-5-7 - ELEVATIONS

1/8" = 1'-0"

AMENTA|EMMA

From: Rich Stevens

To: <u>Elizabeth Sturdy</u>; <u>Emily Beebe</u>; <u>Arozana Davis</u>; <u>Jarrod Cabral</u>; <u>Lynne Budnick</u>

Cc:Barbara Carboni; Chris Lucy; Darrell SheddSubject:RE: 2024-004/ZBA - 113 Castle RoadDate:Wednesday, May 29, 2024 9:08:04 AM

Good Morning Liz,

What a stellar day!!!!

Thank you for the info.

As the contractor has indicated I am in agreement with his solution to this issue.

A very unfortunate and very costly predicament.

I did not feel, however, that I could grant his proposal for temporary occupancy without having the ZBA look at this. Seems like a sensible solution to me.

Unusual but what else is new?

Thanks, Rich

From: Elizabeth Sturdy <ESturdy@truro-ma.gov>

Sent: Wednesday, May 29, 2024 8:33 AM

To: Emily Beebe <EBeeBe@truro-ma.gov>; Rich Stevens <rstevens@truro-ma.gov>; Arozana Davis <ADavis@truro-ma.gov>; Jarrod Cabral <jcabral@truro-ma.gov>

Cc: Barbara Carboni

carboni@truro-ma.gov>; Chris Lucy <CLucy@truro-ma.gov>; Darrell Shedd <dshedd@truro-ma.gov>

Subject: 2024-004/ZBA - 113 Castle Road

Emily, Rich, Zana, Jarrod:

The attached ZBA Application will be reviewed at the June 24, 2024 ZBA meeting at 5:30 pm.

Please respond with any comments you may have, or not. Appreciate any and all input.

Let me know if you have any questions. Thanks,

Elizabeth A. Sturdy (Liz)

Planning Department Assistant

Truro Town Hall

24 Town Hall Road, P.O. Box 2030

Truro, MA 02666

Main: (508) 349-7004, x121 Direct: (508) 214-0935

Fax: (508) 349-5505 esturdy@truro-ma.gov



Town of Truro Zoning Board of Appeals P.O. Box 2030, Truro, MA 02666

APPLICATION FOR HEARING

To the Town Clerk of the Town of Truro, MA

The undersigned hereby files with specific grounds for this application: (check all that apply)

| ı | Office of Town Clerk | |
|---|------------------------|---|
| 1 | 2024-004/ZBA(VAC | |
| | MAY 24 2024 | į |
| 1 | 2:00 PM | |
| | Received TOWN OF TRURO | |
| 1 | 4/14 /12 | |

| GENERAL INFORMATION |
|--|
| □ NOTICE OF APPEAL |
| Applicant is aggrieved by his/her inability to obtain a permit or enforcement action from the Buildin Commissioner on (date) Applicant is aggrieved by order or decision of the Building Commissioner on (date) |
| which he/she believes to be a violation of the Truro Zoning Bylaw or the Massachusetts Zoning Act. |
| PETITION FOR VARIANCE - Applicant requests a variance from the terms § 50.1-6 of the True Zoning Bylaw concerning (describe) height limited the second of the True Zoning Bylaw concerning (describe) |
| ■ APPLICATION FOR SPECIAL PERMIT |
| Applicant seeks approval and authorization of uses under § 50.1-B of the Truro Zoning Byla concerning (describe) height limitations |
| |
| Applicant seeks approval for a continuation, change, or extension of a nonconforming structure or usunder § of the Truro Zoning Bylaw and M.G.L. Ch. 40A, §6 concerning (describe) |
| Property Address 113 Castle Road Map(s) and Parcel(s) 46-398 |
| Registry of Deeds title reference: Book, Page, or Certificate of Tit |
| Number and Land Ct. Lot # and Plan # |
| Applicant's Name Any Holt |
| Applicant's Legal Mailing Address 75 Andrew St. Newton, Mr 02461 |
| Applicant's Phone(s), Fax and Email 617-719-5500 anyholt 4842@gmail. |
| Applicant is one of the following: (please check appropriate box) *Written Permission of the owner is required for submittal of this application. |
| Owner Prospective Buyer* Other* |
| Owner's Name and Address Amy Hot 113 Castle Rd Truco MA 02666 |
| Representative's Name and Address John Ferro 60 Whidah Way Wall Fleet MA |
| Representative's Phone(s), Fax and Email 508-255-8292 Pine Knoll 123 Eginas 1. |
| The applicant is <i>advised</i> to consult with the Building Commissioner, Planning Department, Conservation Department Health Department, and/or Historic Commission, as applicable, prior to submitting this application. |
| Signature(s) John Ferro Amy Holt |
| Applicant(s)/Representative Printed Name(s) Owner(s) Printed Name(s) or written permission |
| Applicant (6)/Representative Signature Camers) Signature or written permission |

To the members of the Zoning Board of Appeals,

My name is John Ferro and I work at Pine Knoll. I am the general contractor for the residential project at 113 Castle Road. The reason I'm coming to this board is due to a height restriction conflict. You'll find all the required information in your packets and a summary of the details below.

The asbuilt data showed top of ridge height of the new construction is 1'-6" over Truro's maximum height tolerance. The first two things that happened next were; 1) Find the cause of the problem and

2) Find a solution.

I reviewed the paperwork and emails and found that I had identified this issue late in the design phase and lowered the pitch of the roof in the drawings, but the truss designer never received the update. So the taller trusses got installed and caused the house to be built 1'-6" over maximum height.

I contacted the truss designer to work out a solution. I had them design an engineered truss adjustment that can be applied to the existing structure to lower the ridge height by 1'-9". This put's the new ridge height 3" below tolerance. The adjustment requires working in the attic and on the roof. Once I had the solution, I went to schedule the labor. The framers were unavailable, so I got on their waiting list.

Since I knew I would not be able to make the correction before the summer, I went back to the building department to see if there was a safe way to get the homeowners in the house temporarily for the summer. We came to a conclusion that included a temporary CO and a notarized letter of intent.

The letter of intent includes;

- A. Complete final inspections for electrical, plumbing, gas, and smoke/fire before homeowners move in for the summer.
- B. Allow homeowners to live in the house for the summer (July, August, and September).
- C. Final energy inspection will be delayed until the ridge is lowered.
- D. Final CO will be delayed until the ridge is lowered and the insulation/energy is completed.
- E. Pine Knoll will make the truss adjustment at no extra cost to the homeowner, between end of summer and end of year.
- F. The homeowners and the general contractor signed and notarized a document laying out these guidelines.

Once I had the letter of intent, the building commissioner said that this should be brought in front of the Zoning Board of Appeals before moving forward.

So I'm not asking the board for a height variance. I am asking for the board's approval to proceed within the guidelines of the notarized letter of intent that I created with the building commissioner. If the only way to do that is to be granted a variance, then I am asking you to grant the variance and I will still abide by the notarized letter of intent.

Thank you for your consideration, John Ferro Pine Knoll



TOWN OF TRURO

Assessors Office Certified Abutters List Request Form



| | | DATE: 5 | 122/24 |
|--------------------------------------|--------------------------|--------------------------------|-------------------------------|
| NAME OF APPLICANT: Am | y Holt | DATE | |
| NAME OF AGENT (if any): | na Ferro | (Pine Knol | 1) |
| MAILING ADDRESS: PO Bo | x 1347 N. | Easthan MA | 02651 |
| CONTACT: HOME/CELL 508 | -255-8292 | EMAIL Prokroll 12 | 23@guay.com |
| PROPERTY LOCATION: 13 | Castle Rd | | |
| | (street | address) | |
| PROPERTY IDENTIFICATION NUM | MBER: MAP 46 | _ parcel 398 | EXTif condominium) |
| ABUTTERS LIST NEEDED FOR: | | FEE: \$ | 15.00 per checked item |
| (please check <u>all</u> applicable) | (Fee must accompar | ny the application unless othe | er arrangements are made) |
| Board of Health ⁵ | Planning Board (PB) | Zoning l | Board of Appeals (ZBA) |
| Cape Cod Commission | Special Permit | | Special Permit ¹ |
| Conservation Commission ⁴ | Site Plan ² | X | Variance ¹ |
| Licensing | Preliminary Su | ıbdivision ³ | |
| Type: | Definitive Sub | division ³ | |
| Other | | | (Fee: Inquire with Assessors) |
| | (Please Specify) | | |
| Note: Per M.G.L., process | ing may take up to 10 ca | lendar days. Please plan | accordingly. |
| THIS SECT | TION FOR ASSESSOR | S OFFICE USE ONLY | |
| Date request received by Assessors: | 5/22/24 D | Pate completed: | |
| List completed by: | 1 100 | Pate paid: 5/22/2014 Co | ash/Check _/5\ |
| Date request received by Assessors: | 5/22/24 D | Pate completed: | ash/Check 15 |

¹Abutters, owners of land directly opposite on any public or private street or way, and abutters to the abutters within 300 feet of the property line.

²Abutters to the subject property, abutters to the abutters, and owners of properties across the street from the subject property.

³Landowners immediately bordering the proposed subdivision, landowners immediately bordering the immediate abutters, and landowners located across the streets and ways bordering the proposed subdivision. Note: For Definitive Subdivision only, responsibility of applicant to notify abutters and produce evidence as required.

⁴All abutters within 300 feet of parcel, except Beach Point between Knowles Heights Road and Provincetown border, in which case it is all abutters within 100 feet. Note: Responsibility of applicant to notify abutters and produce evidence as required.

⁵Abutters sharing any boundary or corner in any direction – including land across a street, river or stream. <u>Note</u>: Responsibility of applicant to notify abutters and produce evidence as required.



TRURO ASSESSORS OFFICE

PO Box 2012 Truro, MA 02666 Telephone: (508) 214-0921

Fax: (508) 349-5506

Date: May 22, 2024

To: John Ferro, Pine Knoll

From: Assessors Department

Certified Abutters List: 113 Castle Road (Map 46 Parcel 398)

Variance

Attached is a combined list of abutters for 113 Castle Road (Map 46 Parcel 398)

The current owners are Paul and Amy Holt.

The names and addresses of the abutters are as of May 17, 2024 according to the most recent documents received from the Barnstable County Registry of Deeds.

Certified by:


Laura Geiges

Assistant Assessor / Data Collector

113 Castle Rd Map 46 Parcel 398 Variance

TOWN OF TRURO, MA BOARD OF ASSESSORS P.O. BOX 2012, TRURO MA 02666

Abutters List Within 300 feet of Parcel 46/398/0



| Key | Parcel ID | Owner | Location | Mailing Street | Mailing City | ST | ZipCd/Country |
|------|------------|--|--------------------|------------------------------------|-----------------|----|---------------|
| 1809 | 42-227-0-R | WALTER & PAMELA THIEVON REV TR TRS: WALTER & PAMELA THIEVON | 120 CASTLE RD | 367 HIGH ST | STIRLING | NJ | 07980 |
| 1810 | 42-228-0-R | POULIN ETHAN & RODERICK ANDREA | 118 CASTLE RD | PO BOX 263 | NO TRURO | MA | 02652-0263 |
| 5684 | 42-301-0-R | ROBERTS FAMILY REV TRUST TRS:ROBERTS RICHARD E & ANNE B | 14 FIRST LIGHT LN | PO BOX 1280 | TRURO | MA | 02666 |
| 1951 | 43-76-0-R | DEERING LEE SCOTT | 20 WHITMANVILLE RD | PO BOX 299 | NO TRURO | MA | 02652 |
| 1952 | 43-77-0-R | PREGENT SARAH & GASPIE RITA & DENNIS & PAUL | 16 WHITMANVILLE RD | c/o DENNIS GASPIE 19 ENSIGN AVE | MECHANICVILLE | NY | 12118 |
| 1953 | 43-78-0-R | CORREA CHRISTOPHER M & KATIE A | 14 WHITMANVILLE RD | PO BOX 880 | NO TRURO | MA | 02652 |
| 5682 | 43-205-0-R | GUBAR MARTIN D & RHODES REBECCA E | 116 CASTLE RD | 54 JORDAN ROAD | BROOKLINE | MA | 02446 |
| 5898 | 43-211-0-R | WOODBURY SCOTT C & JEANNE A | 4 LILY LN | 3 CENTER WOODS NORTH | SAGINAW | MI | 48638 |
| 5899 | 43-212-0-R | WOODBURY SCOTT C & JEANNE A | 2 LILY LN | 3 CENTER WOODS NORTH | SAGINAW | МІ | 48638 |
| 6018 | 43-213-0-R | NADEAU THOMAS J C/O CARPENTER CLYDE TIMOTHY & | 1 LILY LN | 1803 WHITE OAK HOLLOW NE | ATLANTA | GA | 30324 |
| 6019 | 43-214-0-R | BRATSKEIR STANLEY & BRATSKEIR ANNE REZNIKOFF | 3 LILY LN | PO BOX 1276 | TRURO | MA | 02666 |
| 6020 | 43-215-0-R | COSTA PETER M & MELISSA A | 5 LILY LN | 75 WASHINGTON ST, SUITE 100 | PEMBROKE | MA | 02359 |
| 6021 | 43-216-0-R | JCM REAL ESTATE LLC RES AGT: SHARON S MANDLI | 7 LILY LN | 12770 TOUCHSTONE PLACE | WEST PALM BEACH | FL | 33418 |
| 6022 | 43-217-0-R | DUARTE COLLEEN S & PILLOW MICHAEL J | 10 LILY LN | PO BOX 682 | NO TRURO | MA | 02652 |
| 6665 | 43-220-0-R | MOTTA BRANDON F &MAKER SARAH A | 12 WHITMANVILLE RD | PO BOX 930 | NO TRURO | MA | 02652-0930 |

16 5/22/24

| Key | Parcel ID | Owner | Location | Mailing Street | Mailing City | ST | ZipCd/Country |
|------|------------|---|--------------------|--------------------|------------------|----|---------------|
| 6666 | 43-221-0-R | SOUZA JEFFREY J & SOUZA RACHEL C | 10 WHITMANVILLE RD | PO BOX 690 | NO TRURO | MA | 02652 |
| 6667 | 43-222-0-R | A F HULTIN & CO INC | 8 WHITMANVILLE RD | PO BOX 504 | NO TRURO | MA | 02652-0504 |
| 6669 | 43-224-0-R | KANE CARTER T & AN R | 273 RT 6 | PO BOX 456 | TRURÖ | MA | 02666-0456 |
| 2215 | 45-112-0-R | BIKOFSKY LYNN ANNE | 5 FIRST LIGHT LN | PO BOX 364 | TRURO | MA | 02666 |
| 5687 | 45-130-0-R | BRAUER SHELLEY B & HEY JEAN LD | 7 FIRST LIGHT LN | 4 CALVIN RD | JAMAICA PLAIN | MA | 02130-3415 |
| 2229 | 46-1-0-R | MADSEN PETER E | 105 CASTLE RD | PO BOX 1309 | TRURO | MA | 02666 |
| 2519 | 46-310-0-R | TATERKA JAMES ANDREW & TONI M | 112 CASTLE RD | 827 HAIN DR | LAFAYETTE HILL | PA | 19444 |
| 2520 | 46-311-0-R | LEFORT PAUL F & EILEEN M TRS TRS: LEFORT PAUL F & EILEEN M | 1 PERRY RD | 860 SADDLEWOOD DR | GLEN ELYN | IL | 60137 |
| 5681 | 46-373-0-R | WOLFSON JANE | 110 CASTLE RD | 10 BATES ST | CAMBRIDGE | MA | 02140 |
| 6664 | 46-386-0-R | GARVAN STEVEN J & CAREN L | 274 RT 6 | PO BOX 398 | N.TRURO | MA | 02652 |
| 7414 | 46-396-0-R | D MAYERS & L BOWMAN REV TRUST TRS:DAMON MAYERS & LYNN BOWMAN | 101 CASTLE RD | PO BOX 322 | TRURO | МА | 02666 |
| 7416 | 46-397-0-R | HAGHIGHI MOHAMAD T | 109 CASTLE RD | 19 STONEY BROOK RD | HOPKINTON | MA | 01748 |
| 7417 | 46-398-0-R | HOLT PAUL & AMY | 113 CASTLE RD | 75 ANDREW ST | NEWTON HIGHLANDS | MA | 02461 |

42-228-0-R

43-77-0-R

42-301-0-R

43-78-0-R

43-212-0-R

WALTER & PAMELA THIEVON REV TR TRS: WALTER & PAMELA THIEVON 367 HIGH ST STIRLING, NJ 07980

POULIN ETHAN & RODERICK ANDREA PO BOX 263 NO TRURO, MA 02652-0263 ROBERTS FAMILY REV TRUST TRS:ROBERTS RICHARD E & ANNE B PO BOX 1280 TRURO, MA 02666

43-76-0-R

PREGENT SARAH &
GASPIE RITA & DENNIS & PAUL
c/o DENNIS GASPIE

CORREA CHRISTOPHER M & KATIE A
PO BOX 880

DEERING LEE SCOTT PO BOX 299 NO TRURO, MA 02652

19 ENSIGN AVE
MECHANICVILLE, NY 12118

NO TRURO, MA 02652

GUBAR MARTIN D & RHODES REBECCA E 54 JORDAN ROAD BROOKLINE, MA 02446

WOODBURY SCOTT C & JEANNE A 3 CENTER WOODS NORTH SAGINAW, MI 48638 WOODBURY SCOTT C & JEANNE A 3 CENTER WOODS NORTH SAGINAW, MI 48638

43-213-0-R

43-205-0-R

43-214-0-R

43-211-0-R

43-215-0-R

NADEAU THOMAS J C/O CARPENTER CLYDE TIMOTHY & 1803 WHITE OAK HOLLOW NE ATLANTA, GA 30324 BRATSKEIR STANLEY & BRATSKEIR ANNE REZNIKOFF PO BOX 1276 TRURO, MA 02666

COSTA PETER M & MELISSA A 75 WASHINGTON ST, SUITE 100 PEMBROKE, MA 02359

43-216-0-R

43-217-0-R

43-220-0-R

JCM REAL ESTATE LLC RES AGT: SHARON S MANDLI 12770 TOUCHSTONE PLACE WEST PALM BEACH, FL 33418 DUARTE COLLEEN S & PILLOW MICHAEL J PO BOX 682 NO TRURO, MA 02652

MOTTA BRANDON F &MAKER SARAH A PO BOX 930 NO TRURO, MA 02652-0930

43-221-0-R

43-222-0-R

43-224-0-R

SOUZA JEFFREY J & SOUZA RACHEL C PO BOX 690 NO TRURO, MA 02652

A F HULTIN & CO INC PO BOX 504 NO TRURO, MA 02652-0504 KANE CARTER T & AN R PO BOX 456 TRURO, MA 02666-0456

45-112-0-R

45-130-0-R

46-1-0-R

BIKOFSKY LYNN ANNE PO BOX 364 TRURO, MA 02666 BRAUER SHELLEY B & HEY JEAN LD 4 CALVIN RD JAMAICA PLAIN, MA 02130-3415 MADSEN PETER E PO BOX 1309 TRURO, MA 02666

46-310-0-R

46-311-0-R

46-373-0-R

TATERKA JAMES ANDREW & TONI M 827 HAIN DR LAFAYETTE HILL, PA 19444 LEFORT PAUL F & EILEEN M TRS TRS: LEFORT PAUL F & EILEEN M 860 SADDLEWOOD DR GLEN ELYN, IL 60137

WOLFSON JANE 10 BATES ST CAMBRIDGE, MA 02140

46-386-0-R

46-396-0-R

46-397-0-R

GARVAN STEVEN J & CAREN L PO BOX 398 N.TRURO, MA 02652 D MAYERS & L BOWMAN REV TRUST TRS:DAMON MAYERS & LYNN BOWMAN PO BOX 322 TRURO, MA 02666

HAGHIGHI MOHAMAD T 19 STONEY BROOK RD HOPKINTON, MA 01748

46-398-0-R

HOLT PAUL & AMY 75 ANDREW ST NEWTON HIGHLANDS, MA 02461

LG 5/22/24

HOLTPROJECT

105 CASTLE RD.

TRURO, MA

SUMMARY OF CONSTRUCTION REQUIREMENTS

STANDARD FRAMING CONNECTION REQUIREMENTS:

FOLLOW REQUIREMENTS OF TABLE 2 FROM WECM MANUAL.

FLOOR CONSTRUCTION REQUIREMENTS:

FIRST TWO JOIST BAYS OF THE FLOOR FRAMING FROM EACH GABLE END TO BE BLOCKED WITH TJI BLOCKING OR 2x LUMBER 4-ft ON CENTER FOR THE LENGTH OF THE JOIST. SHEATHING TO BE NAILED IN ACCORDANCE WITH TABLE 2 (8d NAILS, 6" SPACING AT THE EDGES AND 12" SPACING IN THE FIELD).

EXTERIOR WALL REQUIREMENTS

ALL EXTERIOR WALL STUDS TO BE 2x6 AT 16" ON CENTER. THE DOUBLE TOP PLATES ON THE EXTERIOR WALLS TO HAVE A MAXIMUM SPLICE LENGTH OF 6 FEET AND SPLICES TO BE NAILED WITH 20-16 & NAILS IN ACCORDANCE WITH TABLE 6 IN THE WFCM 110/B BOOKLET.

ROOF FRAMING REQUIREMENTS:

RAFTER CONNECTION TO THE TOP PLATE REQUIRES SIMPSON H2.5A
HURRICANE CLIPS WITH 2X BLOCKING BETWEEN JOIST BAYS TOE NAILED TO
THE RAFTER AND TOP PLATE WITH 7-IOd NAILS PER BAY. IF BLOCKING IS
NOT DESIRED, SIMPSON H-IOA OR H-I4A HURRICANE CLIPS CAN BE
SUBSTITUTED AND INSTALLED ON EVERY RAFTER WITHOUT BLOCKING. ALL
CLIPS TO BE INSTALL IN ACCORDANCE WITH SIMPSON REQUIREMENTS.

COLLAR TIES ARE REQUIRED IN THE UPPER THIRD OF THE ROOF RAFTERS AND ARE TO BE NAILED WITH (5) IOU NAILS PER SIDE OR USE SIMPSON LSTA 18 STRAPS FROM RAFTER TO RAFTER OVER THE RIDGE BOARD.

ROOF SHEATHING TO BE NAILED USING 8d OR EQUIVALENT NAILS 6" ON CENTER AT THE EDGES, 6" ON CENTER IN THE FIELD. THE FIRST TWO BAYS BETWEEN RAFTERS ARE REQUIRED TO BE BLOCKED 4 FEET ON CENTER AT ALL GABLE ENDS PER THE WFCM.

LIMITATIONS AND CONTRACTOR RESPONSIBILITIES

THE CONTRACTOR MUST REFER TO THE TABLES AND FIGURES WITHIN THE WFCM IIO MPH EXPOSURE B BOOKLET FOR ILLUSTRATIONS AND REQUIREMENTS DISCUSSED WITHIN THIS SUMMARY. ALL CONNECTIONS AND NAILING MUST MEET THE REQUIREMENTS HEREIN AND AS ILLUSTRATED IN THE BOOKLET IN ORDER TO BE IN COMPLIANCE WITH THE BUILDING CODE. THE CONTRACTOR IS RESPONSIBLE TO ENSURE ALL CONNECTIONS, NAILING, AND ANCHOR BOLTS ARE VISIBLE TO THE INSPECTOR AT THE TIME OF THE FRAMING INSPECTION/ FOUNDATION INSPECTION. THE CONTRACTOR MUST REFERENCE THE SIMPSON STRONG TIE C-2014 CATALOG FOR ALL STRAP, HANGAR, AND TIE INSTALLATION REQUIREMENTS AND LIMITATIONS. THIS DOCUMENT AND THE ATTACHMENTS AS WELL AS A COPY OF THE WFCM BOOKLET MUST ACCOMPANY ALL SETS OF PLANS SUBMITTED TO THE BUILDING DEPARTMENT AND ISSUED TO THE

CONTRACTOR/ SUBCONTRACTORS UNLESS THE PLANS ARE UPDATED WITH NOTES AND DETAILS THAT REFLECT THE REQUIREMENTS STATED IN THIS DOCUMENT AND ATTACHMENTS.

AWC Guide to Wood Construction in High Wind Areas: 110 mph Wind Zone Massachusetts Checklist for Compliance (780 CMR 5301.2.1.1)

| WIND SPEED (3-SEC. GUST) | IIO MPH | X |
|---|--|---------------------------------------|
| WIND EXPOSURE CATEGORY | В | X |
| 1.2 APPLICABILITY | | |
| | PRES ≤ 2 STORES | <u> </u> |
| ROOF PITCH MEAN ROOF HEIGHT | _4: 2_ ≤ 2: 2 22_ft ≤33' | |
| BUILDING WIDTH, W | 48 ft ≤80' | |
| BUILDING LENGTH, L | 50 ft ≤80' | X |
| BUILDING ASPECT RATIO (L/W) | <u>-50</u> :05:1 ≤3:1 | X |
| NOMINAL HEIGHT OF TALLEST OPENING | <u>6'8"</u> ≤6'8" | X |
| 1.3 FRAMING CONNECTIONS GENERAL COMPLIANCE WITH FRAMING CONNE | EC110NS | X |
| 2.1 FOUNDATION | | |
| FOUNDATION WALLS MEET REQ. OF 780 CMF | R 5404.1 - CONCRETE | |
| 2.2 ANCHORAGE TO FOUNDATIONI,3 | | |
| 5/8" ANCHOR BOLTS IMBEDDED OR 5/8" F MECHANICAL ANCHORS AS AN ALTERNATIVE IN | | |
| BOLT SPACING — GENERAL | <u>54</u> in. o.c. | X |
| BOLT SPACING FROM END/JOINT OF PLATE | 9 in, ≤ 6 " - $ 2$ " | X |
| BOLT EMBEDMENT - CONCRETE | _7_ in, ≥ 7" | <u> </u> |
| PLATE WASHER (FIG 5) | ≥ 3" X 3" X ¼" | <u> </u> |
| 3.1 FLOORS | | \ |
| FLOOR FRAMING MEMBER SPANS CHECKED | | <u>X</u> |
| MAXIMUM FLOOR OPENING DIMENSION FULL HEIGHT WALL STUDS AT FLOOR OPENING | <u>10</u> ft ≤ 12-ft | X |
| LESS THAN 2' FROM EXTERIOR WALL | 1) | Χ |
| MAX. FLOOR JOIST SETBACKS SUPPORTING | | |
| LOAD BEARING OR SHEAR WALLS | N/A ft $\leq d$ | N/A |
| MAX. CANTILEVERED JOISTS SUPPORTING | | · · · · · · · · · · · · · · · · · · · |
| LOAD BEARING OR SHEAR WALLS | N/A ft $\leq d$ | N/A |
| FLOOR BRACING AT ENDWALLS | | X |
| FLOOR SHEATHING TYPE | | |
| FLOOR SHEATHING THICKNESS | <u>3/4</u> in. | |
| FLOOR SHEATHING FASTENING 8 d NAILS AT 6 in. ED | PGE / 12 in. FIELD | X |
| 4.1 WALLS | | |
| WALL HEIGHT | | |
| LOADBEARING WALLS | <u>9</u> ft ≤ 10' | <u>X</u> |
| NON-LOADBEARING WALLS | <u>9</u> ft ≤ 20" | <u>X</u> |
| WALL STUD SPACING | $\underline{16} \text{ in.} \leq 24 \text{"o.c}$ | X |
| WALL STORY OFFSETS | N/A ft $\leq d$ | <u> N/ A</u> |
| 4.2 EXTERIOR WALLS3 | | |
| WOOD STUDS | - 8 ft 0 : | V |
| LOADBEARING WALLS 2 x <u>6</u> NON-BEARING WALLS 2 x 6 | - <u>8</u> ft <u>9</u> in. - <u>8</u> ft <u>9</u> in. | X |
| GABLE END WALL BRACING | | |
| FULL HEIGHT ENDWALL STUDS | | Χ |
| | 100 % ≥ 0.9W | X |
| I X 3 CEILING FURRING STRIPS @ 16" S | | <u> </u> |
| BLOCKING @ 4 ft. SPACING IN END JO | OIST / TRUSS BAYS | X |
| DOUBLE TOP PLATE | | |
| SPLICE LENGTH | <u>6</u> ft | <u> </u> |
| SPLICE CONNECTION (# 16D COMMO | ON NAILS) 20 | X |

| ompliance (780 CMR | 5301.2.1.1) | |
|--|--|-----------------|
| LOADBEARING WALL CONNECTIONS | | |
| LATERAL (# 16d COMMON | NALS)2 | X |
| NON-LOADBEARING WALL CONNECT | 10N5 | |
| LATERAL (# 16d COMMON | NAILS)2 | <u> </u> |
| LOAD BEARING WALL OPENINGS | | V |
| HEADER SPANS | <u> 0 </u> | <u>X</u> |
| SILL PLATE SPANS | <u> 0</u> ft <u>0</u> in,≤ -f | <u>X</u> |
| FULL HEIGHT STUDS NON-LOAD BEARING WALL OPENING | <u>4</u> | X |
| HEADER SPANS | 1) ft 0 in,≤ 2-ft | X |
| SILL PLATE SPANS | $\frac{1}{ } \text{ ft } 0 \text{ in. } \leq 2\text{-ft} $ | <u> </u> |
| FULL HEIGHT STUDS (NO. OF | - | X |
| EXTERIOR WALL SHEATHING TO RESIS | | DUSLY |
| MINIMUM BUILDING DIMENSIO | 2N (W) | |
| HEIGHT OF TALLEST | OPENING <u>6'8"</u> ≤ 6'8" | <u> </u> |
| SHEATHING TYPE | <u>WSP</u> | <u> </u> |
| EDGE NAIL SPACING | | <u> </u> |
| FIELD NAIL SPACING | | <u> </u> |
| SHEAR CONNECTION | | <u>X</u> |
| PERCENT FULL-HEIGH | | <u>X</u> |
| MAXIMUM BUILDING DIMENSI | PENINGS > 6'8" | |
| HEIGHT OF TALLEST | | Y |
| SHEATHING TYPE | W5P | <u> </u> |
| EDGE NAIL SPACING | | X |
| FIELD NAIL SPACING | | X |
| SHEAR CONNECTION | 1(#16d/ft) <u>3</u> | X |
| PERCENT FULL-HEIGH | H SHEATHING 30 | <u> </u> |
| -5% FOR O | PENINGS > 6'8" | X |
| WALL CLADDING | | |
| RATED FOR WIND SPEED? | MECLENI CHE AMININI I CINCEM | X |
| APA PORTAL WALLS AND/OR WIND | DESIGN SHEARWALLS USED | <u>YES</u> |
| 5.1 ROOFS | | |
| ROOF FRAMING MEMBER SPANS CHE | CKED? | X |
| ROOF OVERHANG I ft. | ≤ SMALLER OF 2-ft OR L/3 | X |
| TRUSS OR RAFTER CONNECTIONS AT | LOAD BEARING WALLS | |
| PROPRIETARY CONNECTORS | | |
| UPLIFT | U= 370 plf | <u> </u> |
| LATERAL | L= 176 plf | <u> </u> |
| SHEAR | S= 77 plf | <u>X</u> |
| RIDGE STRAPS (IF COLLAR TIES NOT | ' | <u>X</u> |
| GABLE RAKE OLITLOOKER I_ ft : 1RUSS OR RAFTER CONNECTIONS AT | | X |
| PROPRIETARY CONNECTORS | NON LURVILING WILL) | |
| UPLIFT | | N/A |
| LATERAL (#16d CON | MMON NAILS) | N/A |
| ROOF SHEATHING TYPE | WSP | X |
| ROOF SHEATHING THICKNESS | 7/16 in.≥7/1 <mark>6"</mark> WSP | X |
| ROOF SHEATHING FASTENING | | X |
| NOTES: | | |
| I. THIS CHECKLIST SHALL BE MET IN ITS ENTIRE | | |
| 780 CMR 5301.2.1.1 ITEM 1. IF THE CHECKLIS | | |
| METAL STRAPS AND HOLD DOWNS ARE NOT I | REQUIRED PER THE WFCM 110 MPI | H GUIDE: |
| a. STEEL STRAPS PER FIGURE 5 | | |
| b. 20 GAGE STRAPS PER FIGURE II | | |
| c. UPLIFT STRAPS PER FIGURE 14 d. ALL STRAPS PER FIGURE 17 | | |
| e. CORNER STUD HOLD DOWNS PER F | FIGURE IRA AND FIGURE IRB | |
| 2. THE BOTTOM SILL PLATE IN EXTERIOR WAL | | OMINAL. |
| 1HICKNESS PRESSURE TREATED #2-GRADE. | 1 II VV VV I I IVIII VIIVIUIVI Z II VI I VV | ✓ / V III N/ 1/ |
| THE CHIEF CHIEF THE PROPERTY OF THE PROPERTY O | | 40LLC (4.0) |

3. SEE CHECKLIST SHEARWALL CONSTRUCTION DETAIL FOR SHEARWALL CONSTRUCTION

THIS REVIEW WAS COMPLETED ON PLANS SUBMITTED BY PINE KNOLL BUILDERS AND WAS BASED ON THE FLOOR PLANS AND ELEVATIONS PROVIDED. ANY CHANGES TO THESE PLANS OR FIELD CHANGES MADE MAY RENDER THE REQUIREMENTS OUTLINED IN THIS DOCUMENT NULL AND VOID AND COULD RESULT IN NON-COMPLIANCE WITH THE REQUIREMENTS OF THE WIND DESIGN.

SHEARWALL PANEL NAILING SCHEDULE

6/12

¹⁵/₃₂" PLYWOOD NAILED WITH 8d COMMON OR GALVANIZED BOX NAILS AT 6"O.C. AT THE EDGES AND 12" O.C. IN THE FIELD.



 $^{15}\!\!/_{32}$ " PLYWOOD NAILED WITH 8d COMMON OR GALVANIZED BOX NAILS AT 4"O.C. AT THE EDGES AND 12" O.C. IN THE FIELD.



 $^{15}\!\!/_{32}$ " PLYWOOD NAILED WITH 8d COMMON OR GALVANIZED BOX NAILS AT 3"O.C. AT THE EDGES AND 12" O.C. IN THE FIELD.

NOTE: FOR PLYWOOD SHEAR WALLS LISTED ABOVE, 8d COMMON OR GALVANIZED BOX NAILS = $(0.131 \times 21/2^{11})$. GUN NAILS MATCHING THE NAIL DIAMETER AND LENGTH MAY BE USED AS A SUBSTITUTE.

NOTE: ALL PLYWOOD TO BE RUN VERTICAL FROM SILL PLATE TO AT LEAST 2" INTO THE SECOND FLOOR BOX ON TWO STORY BUILDINGS OR TO THE DOUBLE TOP PLATE IN SINGLE STORY BUILDINGS. USE 2 ROWS OF NAILS SPACED 3" ON CENTER STAGGERED AT THE TOP AND BOTTOM OF EACH PLYWOOD SHEET PER FIGURE 4 IN THE CHECKLIST.

SOLE PLATE CONNECTION SCHEDULE

CONNECTION TO FLOOR RIM BOARD

WALL TYP

WALL TYPE SOLE PLATE CONNECTION TO RIM BOARD

6/12

(3) - 16d COMMON NAILS PER 16"

4/12

(3) - 16d COMMON NAILS PER 16"



(4) - 16d COMMON NAILS PER 16"

CONNECTION TO CONCRETE FOUNDATION

FOUNDATION SILL PLATE CONNECTION TO CONCRETE

8" DIA, ANCHOR BOLTS AT 54" O.C.,

 $\frac{\text{NOTE}}{\text{NOTE}}: \text{ANCHOR BOLTS REFERENCED ABOVE TO BE} \\ \frac{5}{8}" \text{ DIAMETER A307 STEEL} \\ \text{ANCHOR BOLTS WITH 3" x 3" x } \\ \frac{1}{4}" \text{ PLATE WASHERS WITH 7" MINIMUM EMBEDMENT INTO CONCRETE.} \\ \\$

SHEARWALL CONSTRUCTION

I - ALL SHEARWALLS TO HAVE DOUBLE TOP PLATES AND DOUBLE 2X STUDS AT EACH END OF THE WALL.

2 - FACE NAIL DOUBLE TOP PLATES W/ 16d NAILS AT 16" O.C.

3 - NAILING OF SHEATHING TO BE CONTINUED ABOVE AND BELOW ALL OPENINGS IN SHEARWALL.

4 - ATTACH DOUBLE 2X STUDS AND BUILT-UP CORNER STUDS AT SHEARWALL ENDS WITH
(2) 16d NAILS AT 6" O.C. FOR ATTIC/SECOND FLOOR SHEARWALLS AND (2) 16d
NAILS AT 4" O.C. STAGGERED FOR FIRST FLOOR SHEARWALLS.

KING AND JACK STUD REQUIREMENTS

XK,XJ # OF KING AND JACK STUDS AT OPENINGS. USE 2K, IJ IF NOT NOTED OTHERWISE


CHECKLIST COVER SHEET PROJECT: HOLT PROJECT

PROJECT ADDRESS:

105 CASTLE RD. TRURO, MA



P.O. BOX 1879 44 UNDERPASS RD UNIT 2 BREWSTER, MA 02631 (774) 353-2144



| JOB#: 22-051 | SHEET |
|-----------------|-------|
| DATE:03-11-2022 | CS1.0 |
| SCALE: NONE | |

CHECKLIST SHEARWALL CONSTRUCTION


I, FROM TABLES IO AND II WECM MANUAL IIO MPH EXP. B AND LOCATION OF WALL SHEATHING AND BUILDING ASPECT RATIO, DETERMINE PERCENT FULL-HEIGHT SHEATHING AND NAIL SPACING REQUIREMENTS


2. WOOD STRUCTURAL PANELS SHALL BE MINIMUM THICKNESS OF 7/16" AND BE INSTALLED AS FOLLOWS:

- a. PANELS SHALL BE INSTALLED WITH STRENGTH AXIS PARALLEL TO STUDS.
- 6. ALL HORIZONTAL JOINTS SHALL OCCUR OVER AND BE NAILED TO FRAMING.
- c. ON SINGLE STORY CONSTRUCTION, PANELS SHALL BE ATTACHED TO BOTTOM PLATES AND TOP MEMBER OF THE DOUBLE TOP PLATE.
- d. ON TWO STORY CONSTRUCTION, UPPER PANELS SHALL BE ATTACHED TO THE TOP MEMBER OF THE UPPER DOUBLE TOP PLATE AND TO BAND JOIST AT BOTTOM OF PANEL, UPPER ATTACHMENT OF LOWER PANEL SHALL BE MADE TO BAND JOIST AND LOWER ATTACHMENT MADE TO LOWEST PLATE AT FIRST FLOOR FRAMING.


e. HORIZONTAL NAIL SPACING AT DOUBLE TOP PLATES, BAND JOISTS, AND GIRDERS SHALL BE A DOUBLE ROW OF 8D STAGGERED AT 3 INCHES ON CENTER PER FIGURES BELOW: VERTICAL AND HORIZONTAL NAILING FOR PANEL ATTACHMENT

VERTICAL AND HORIZONTAL NAILING FOR PANEL ATTACHMENT







STRUCTURAL RIDGE BEAM



RAFTER TO TOP PLATE



ELEVATION VIEW



SHEARWALL HOLDDOWN SCHEDULE

SECOND FLOOR AND INTERIOR HOLDDOWNS

- (1) CS 16 COIL STRAP W/ (26) 8d Q.131 x 21/3" LONG) NAILS WITH STRAP APPLIED DIRECTLY TO 2X FRAMING MEMBERS, PROVIDE HALF OF THE NUMBER OF NAILS SPECIFIED. AT EACH END OF STRAP. CUT SMALL SLOT IN FLOOR SHEATHING AND ATTACH STRAP TO LVL BEAM OR LVL BLOCKING IN BETWEEN TJI FLOOR JOISTS IN PLOOR FRAMING BELOW. CONNECT BLOCKING TO TJI JOIST WEBS WITH HUS 412 FACE MOUNTHANGER. PROVIDE BACKER BLOCKING IN TJI JOIST WEB PER MANUFACTURER'S SPECIFICATION
- (2) C5 16 COIL STRAP W/ (26) 8d (0.131 x 21/2" LONG) NAILS WITH STRAP APPLI 2) DIRECTLY TO 2X FRAMING MEMBERS, PROVIDE HALF OF THE NUMBER OF NAILS SPECIFIED AT EACH END OF STRAP. CUT SMALL SLOT IN FLOOR SHEATHING AND ATTACH STRAP TO BEAM OR LVL BLOCKING IN BETWEEN TJI FLOOR JOISTS IN FLOOR FRAMING BELOW CONNECT BLOCKING TO TJI JOIST WEBS WITH HUS 412 FACE MOUNT HANGER, PROVIDE BACKER BLOCKING IN TJI JOIST WEB PER MANUFACTURER'S SPECIFICATIONS

---- SHEARWALL

EARWALL GRIDLINE

FOUNDATION HOLDDOWNS

- HDU4-SD52,5 W/ SSTB2O ANCHOR BOLT PLACED BEFORE POUR, ATTACH TO FOUNDATION W/ APPLICABLE ANCHORMATE, USE CAW COUPLER NUT BETWEEN ANCHOR BOLT AND 21 THREADED ROD INTO HOLDOW
- STHD14 FOUNDATION HOLDOWN STRAPS FOR APA PORTAL WALLS, SEE TT-100F FOR (14) ADDITIONAL CONSTRUCTION DETAILS, ATTACH HOLDOWNS TO FOUNDATION FORMWORK WITH APPROPRIATE ANCHORMATES PRIOR TO POUR
- HDU14-SDS2.5 ATTACHED TO 6x6 DOUGLAS-FIR POST W/ SBIX30 ANCHOR BOLT PLACED BEFORE POUR. ATTACH TO FORM WORK WITH APPLICABLE ANCHORMATE. USE CNW I'' COURLER NUT BETWEEN ANCHOR BOLT AND I'' THREADED ROD INTO HOLDOWN.


XK, XJ # OF KING AND JACK STUDS AT OPENINGS

LEGEND


PERFORATE SHEARWALL. CONTINUE PLYWOOD ABOVE AND BELOW SHEARWALL HOLDDOWN TYPE OPENING WITH NAILING ACCORDING TO SPECIFIED SHEARWALL TYPE.

APA PORTAL WALL DETAIL (NOT TO SCALE)

(SUBSERVIENT TO APA TT-100F BY THE ENGINEERED WOOD ASSOCIATION)



MOMENT FRAME CONSTRUCTION DETAIL (EXAMPLE ONLY, NOT TO SCALE)



ONAL Н


> DATE REVISION/ISSUE

PROJECT ADDRESS:


105 CASTLE RD. TRURO, MA




P.O. BOX 1879 44 UNDERPASS RD UNIT 2 BREWSTER, MA 02631 (774) 353-2144



SHEET JOB#: 22-051 CS1.1 DATE:03-11-2022 SCALE: NONE






DATE: 2/15/2022

P.O.BOX 1347 N. EASTHAM MA 02651

4



DRAWN BY: John Ferro 2/15/2022

DATE:

P.O.BOX 1347 N. EASTHAM MA 02651

FIRST FLOOR **FINISH SCHEDULE**

SECOND FLOOR FINISH SCHEDULE

4

DRAWN BY: John Ferro SCALE: 3/16" = 1'-0"

DATE: 3

2/15/2022

P.O.BOX 1347 N. EASTHAM MA 02651

Paul & Amy Holt 113 Castle Rd, Truro MA 02666

PLAYROOM + WORKOUT AREA

FLOORS - CARPET + RUBBER FLOOR IN WORKOUT AREA WALLS - SHEETROCK **CEILING - SHEETROCK** LIGHTS - RECESSED

BATH 1

FLOORS - TILE WALLS - SHEETROCK **CEILING - SHEETROCK** LIGHTS - RECESSED + **VANITY LIGHTS**

UNFINISHED BASEMENT

FLOORS - CONCRETE SLAB WALLS - CONCRETE **CEILING - UNFINISHED** LIGHTS - 4' LONG TUBE LIGHTS

SUNROOM:

FLOORS - HARD WOOD WALLS - SHEETROCK FIRE PLACE FINISH - STONE CEILING - CATHEDRAL CEILING FINISH - NATURAL WOOD CEILING FAN - YES LIGHTS - RECESSED

LIVING ROOM:

FLOORS - HARD WOOD WALLS - SHEETROCK FIRE PLACE FINISH - STONE CEILING - SHEETROCK LIGHTS - RECESSED

KITCHEN:

FLOORS - HARD WOOD WALLS - SHEETROCK, BACKSPLASH TILE + SOFFIT ABOVE WALL CABS (SIZE: TBD) CEILING - SHEETROCK LIGHTS - RECESSED + (2) PENDANT LIGHTS

DINING ROOM:

FLOORS - HARD WOOD WALLS - SHEETROCK CEILING - SHEETROCK LIGHTS - HANGING FIXTURE

BATH 2:

FLOORS - TILE WALLS - SHEETROCK + BACKSPLASH TILE CEILING - SHEETROCK | CEILING FAN - YES |LIGHTS - RECESSED + ||LIGHTS - RECESSED **VANITY LIGHTS**

FOYER:

FLOORS - OAK WALLS - SHEETROCK **CEILING - SHEETROCK LIGHTS - RECESSED**

GARAGE:

FLOORS - CONCRETE WALLS - SHEETROCK **CEILING - SHEETROCK** LIGHTS - TBD

BEDROOM 1:

FLOORS - CARPET WALLS - SHEETROCK CEILING - SHEETROCK

1/2 BATH 1 + W/D ROOM:

FLOORS - TILE WALLS - SHEETROCK **CEILING - SHEETROCK** LIGHTS - RECESSED

MUDROOM:

FLOORS - TILE WALLS - SHEETROCK CEILING - SHEETROCK LIGHTS - RECESSED

BEDROOMS 2, 3, 4, & 5

FLOORS - HARD WOOD WALLS - SHEETROCK CEILING - CATHEDRAL, WOOD BEAMS, SHEETROCK CEILING FAN: YES (1/ea) LIGHTS - RECESSED

BATHS 3, 4, & 5

FLOORS - TILE WALLS - SHEETROCK CEILING - SHEETROCK LIGHTS - RECESSED + **VANITY LIGHTS**

DECKS + WIDOWS WALK:

DECK - HEAT RESISTANT (GREY) COMPOSITE DECKING POSTS - PRESSURE TREATED RAILING - WOOD POST W/ CABLE RAILING

SITTING ROOM + HALLWAYS:

FLOORS - HARD WOOD WALLS - SHEETROCK CEILING - CATHEDRAL + NATURAL WOOD CEILING FAN: YES LIGHTS - RECESSED

DATE: 2/15/2022

| aul & Amy Holt | 113 Castle Rd, | Truro MA | 02666 |
|----------------|----------------|----------|-------|
| Ø | | | |


| | | | | WINDOW SCHEDULE | | |
|----------------------------|------------|--------------------------|-------|---|-----------------------|-----------------------------|
| | OPENING ID | PRODUCT CODE | COUNT | LIBRARY NAME | TYPE | R.O. SIZE |
| count as 15 - | 3 | TW2852 | 1 | Manufacturer\Andersen\400-Tilt-Wash Double Hung | WINDOW | R.O. 2'-10 1/8" x 5'-4 7/8" |
| | 4 | TW2842 | 16 | Manufacturer\Andersen\400-Tilt-Wash Double Hung | WINDOW | R.O. 2'-10 1/8" x 4'-6 7/8" |
| | 5 | TW210510 | 6 | Manufacturer\Andersen\400-Tilt-Wash Double Hung | WINDOW | R.O. 3'-0 1/8" x 6'-0 7/8" |
| | 6 | TW2842-3 | 2 | Manufacturer\Andersen\400-Tilt-Wash Double Hung | WINDOW | R.O. 8'-6 7/8" x 4'-6 7/8" |
| | 8 | CTC3 (Half Round) | 1 | Manufacturer\Andersen\400-Casement_Awning Picture_Transom Windows | WINDOW | R.O. 6'-0 3/8" x 3'-2 3/4" |
| | 9 | PTR3010 | 1 | Manufacturer\Andersen\400-Casement_Awning Picture_Transom Windows | WINDOW | R.O. 3'-0 1/2" x 1'-0 1/2" |
| | 15 | TW2852 | 5 | Manufacturer\Andersen\400-Tilt-Wash Double Hung | WINDOW | R.O. 2'-10 1/8" x 5'-4 7/8" |
| | 19 | G65 + 1'-6" Transom | 2 | Manufacturer\Andersen\400-Gliding Windows + 1'-6" Transom | COMBINED UNIT | R.O. 6'-0" x 6'-6 1/8" |
| | 21 | PTR5010 | 1 | Manufacturer\Andersen\400-Casement_Awning Picture_Transom Windows | WINDOW | R.O. 5'-0 3/8" x 1'-0 1/2" |
| | 22 | FLX 10'x4' | 1 | Manufacturer\Andersen\400-Flexiframe 10'x4' | WINDOW | R.O. 10'-0 1/2" x 4'-0 5/8" |
| | 29 | TW2832 | 1 | Manufacturer\Andersen\400-Tilt-Wash Double Hung | WINDOW | R.O. 2'-10 1/8" x 4'-6 7/8" |
| | 34 | TW2852-3 | 1 | Manufacturer\Andersen\400-Tilt-Wash Double Hung | WINDOW | R.O. 8'-6 7/8" x 5'-4 7/8" |
| oundation windows — | 35 | 36X24 SLIDER | 8 | Window\Slider | SLIDING WINDOW | R.O. 3' 0" x 2' 0" |
| | 36 | DHP56410 + 1'-6" Transom | 2 | Manufacturer\Andersen\400-Tilt-Wash DH Picture_Transom Windows | COMBINED UNIT | R.O. 5'-7 7/8" x 6'-7" |
| | 38 | G55 + 1'-6" Transom | 4 | Manufacturer\Andersen\400-Gliding Windows + 1'-6" Transom | COMBINED UNIT | R.O. 5'-0" x 6'-6 1/8" |
| front door transom - | 41 | DHT41010-MODIFIED | 1 | Manufacturer\Andersen\400-Tilt-Wash DH Picture_Transom Windows | WINDOW | R.O. 5'-0" x 2'-0" |
| | 44 | G42 | 1 | Manufacturer\Andersen\400-Gliding Windows | SLIDING WINDOW | R.O. 4'-0" x 1'-11" |
| | 45 | G43 | 2 | Manufacturer\Andersen\400-Gliding Windows | SLIDING WINDOW | R.O. 4'-0" x 3'-0" |
| | 50 | VS606 | 1 | Velux Skylight S606 | Skylight | R.O. 44 1/4" x 45 3/4" |


| DOORS SCHEDULE | | | | | |
|----------------|--|-------|--|---------------|---------------------|
| OPENING ID | PRODUCT CODE | COUNT | LIBRARY NAME | TYPE | R.O. SIZE |
| A | 72X80 SLIDING GLASS 2 | 1 | Exterior Door\Patio | SLIDING DOOR | R.O. 6'-0" x 6'-8" |
| В | 30X80 COLONIAL A 1 | 17 | Interior Door\Colonial | DOOR | R.O. 2'-8" x 6'-9" |
| D | 30X80 COLONIAL POCKET 1 | 8 | Interior Door\Pocket | POCKET | R.O. 5'-0" x 6'-8" |
| E | 36X80 COUNTRY A 1 + 1'-6" Transom | 2 | Exterior Door\Country | COMBINED UNIT | R.O. 3'-3" x 8'-8" |
| F | 36X80 COUNTRY A 1 No Grilles Transom MODIFIED | 1 | Exterior Door\Country | COMBINED UNIT | R.O. 3' 3" x 8' 8" |
| | 60X80 LH ENTRY - 2 SL-MODIFIED + 1'-6" Transom | 1 | Exterior Door\Entry | COMBINED UNIT | R.O. 5'-0" x 6'-9" |
| L | 60X80 BIFOLD COLONIAL 2 | 1 | Interior Door\Bifold | BIFOLD | R.O. 5'-0" x 6'-8" |
| M | 54X80 BIFOLD COLONIAL 2 | 1 | Interior Door\Bifold | BIFOLD | R.O. 4'-6" x 6'-8" |
| ?? R ?? | 36X80 COUNTRY A 1-No Grilles (2x6 Wall) | 1 | Exterior Door\Country | DOOR | R.O. 3'-3" x 6'-9" |
| Т | 30X80 BIFOLD COLONIAL 1 | 2 | Interior Door\Bifold | BIFOLD | R.O. 2'-6" x 6'-8" |
| U | 42X80 BIFOLD COLONIAL 2 | 2 | Interior Door\Bifold | BIFOLD | R.O. 3'-6" x 6'-8" |
| Z | FWG120611-4 SAAS + 1'-6" Transom | 2 | Manufacturer\Andersen\400-Frenchwood Gliding Patio Doors | COMBINED UNIT | R.O. 11'-9" x 8'-8" |



LEFT ELEVATION SCALE: 1/8" = 1'-0"

RIGHT ELEVATION SCALE: 1/8" = 1'-0"






4

DATE: 2/15/2022 DRAWN BY:

P.O.BOX 1347 N. EASTHAM MA 02651




CROSS SECTION E SCALE: 1" = 5'-0"

DRAWN BY: John Ferro

DATE: 2/15/2022

SCALE: 1" = 5'-0"

PINE KNOLL DEVELOPERS



DRAWN BY: John Ferro


PINE KNOLL DEVELOPERS
P.O.BOX 1347 Phone: 508-255-8292
N. EASTHAM Fax: 508-255-8292
MA 02651 Email: pineknoll123@gmail.com


DATE: 2/15/2022

SCALE: 1/4" = 1'-0"

Paul & Amy Holt 113 Castle Rd, Truro MA 02666

CROSS SECTION F SCALE: 1/4" = 1'-0"





PINE KNOLL DEVELOPERS

P.O.BOX 1347 N. EASTHAM MA 02651

DRAWN BY: John Ferro

DATE: 2/15/2022

Revisions:

Boise Cascade

PLANS BASED ON ARCHITECTURAL SET DATED Plans Date

13/14

DRAWN BY: John Ferro SCALE: 1/8" = 1'-0"

DATE: 2/15/2022

SOFT PESIGN SOFTWARE

Paul & Amy Holt 113 Castle Rd, Truro MA 02666

SALES PRESENTATION DRAWING
This placing plan is provided as a courtesy to the Builder. It is
intended to indicate product selection and placement. No
structural or dimensional check has been made with the design
drawings of the building. It is the responsibility of the Customer
to review and approve all bearing conditions, connections,
spans, loading, product usages, and quantities. This drawing
has not been checked by Boise Cascade Engineering

3 Castle Road Truro, MA

BC FRAMER Scale: 1/4" = 1'-0" Date: 1/14/22 By: KLL Sheet: 2/2

Mid-Cape

Experience

that Builds.

SECOND FLOOR FRAMING PLAN 14" AJS-20/AJS-25 @ 16"/12" <u>O.C.</u>

| Products | | | | | | |
|----------|---------|-------------------------------------|--------|-------|--|--|
| PlotID | Net Qty | Product | Length | Plies | | |
| J40 | 16 | 14" AJS® 20 | 40' 0" | 1 | | |
| J16 | 13 | 14" AJS® 20 | 16' 0" | 1 | | |
| J10 | 6 | 14" AJS® 20 | 10' 0" | 1 | | |
| J6 | 5 | 14" AJS® 20 | 6' 0" | 1 | | |
| J26 | 18 | 14" <i>A</i> JS® 25 | 26' 0" | 1 | | |
| FB1-3 | 3 | 1-3/4" x 14" VERSA-LAM® 2.0 3100 SP | 26' 0" | 3 | | |
| FB2-3 | 3 | 1-3/4" x 14" VERSA-LAM® 2.0 3100 SP | 22' 0" | 3 | | |
| FB3-2 | 4 | 1-3/4" x 14" VERSA-LAM® 2.0 3100 SP | 16' 0" | 2 | | |
| FB4-2 | 2 | 1-3/4" x 14" VERSA-LAM® 2.0 3100 SP | 8' 0" | 2 | | |
| Rim1 | 13 | 1-1/8" x 14" BC RIM BOARD OSB | 12' 0" | 1 | | |

| Connector Summary | | | | |
|-------------------|-----|---------|-------------|--|
| PlotID | Qty | Manuf | Product | |
| H1 | 4 | Simpson | HHUS410 | |
| H2 | 24 | Simpson | IUS2.56/14 | |
| Н3 | 14 | Simpson | IUS2.56/9.5 | |
| H4 | 18 | Simpson | IUS3.56/14 | |




*** **FOR REVIEW** ***

- ☐ Beam sizes changed from specification ☐ Steel or flitch beams by others required ☐ Joist depth changed☐ Joist direction changed☐ ☐ Flush beams deeper than floor joists ☐ Verify Post and or column locations Joist series changed Joist spacing changed
- ☐ Posts added (see notes on plan)
 ☐ Verify joists and beam lengths Beams added for structural reasons ☐ Mid span bridging recommended ☐ Verify design criteria Critical dimensions have been scaled Note high deflection ☐ Verify framing at fireplace ☐ Verify framing at stairwell ☐ Connection by others req'd
- ☐ Additional information required to complete joist layout

☐ Shop drawing is an estimate only, not for construction ☐ Based on truss roof system

PINE KNOLL DEVELOPERS

P.O.BOX 1347 Phone: 508-255-8292 N. EASTHAM Fax: 508-255-8292 MA 02651 Email: pineknoll123@gmail.com



PINE KNOLL DEVELOPERS

P.O.BOX 1347 Phone: 508-255-8292 N. EASTHAM Fax: 508-255-8292 MA 02651 Email: pineknoll123@gmail.com

DATE: 2/15/2022

DRAWN BY: John Ferro SCALE: 1/8" = 1'-0"

14/1 -SECTION LETTER

EXHIBIT 1

TOWN OF TRURO APPLICATION FOR A CURB CUT PERMIT

<u>Note:</u> This permit application must be accompanied by a plan. If this permit is being applied for by someone other than the Owner of the property, the owner's signature must appear at the bottom of the application.

Date: __4/7/22

| To the Board of Selectmen 24 Town Hall Road P. O. Box 2030 Truro, MA 02666 | | | | | |
|---|--|--|--|--|--|
| Re: APPLICATION FOR A CURB CUT | | | | | |
| Dear Board Members: | | | | | |
| The applicant(s) hereby make application for a curb cut as follows: | | | | | |
| Owners Name(s) (Please Print): Paul & Amy Holt | | | | | |
| Address: 75 Andrew St. Newton, MA 02461 | | | | | |
| Phone Number: 617-719-5500 | | | | | |
| Email Address: amyholt4842@gmail.com | | | | | |
| Curb Cut Street Location: 113 Castle Rd. Truro | | | | | |
| Affected Town or State road: Castle Rd | | | | | |
| Truro Assessor's Map Number: 46 Parcel Number: 398 | | | | | |
| Name of contractor: Pine Knoll Dev. | | | | | |
| Contractor Phone Number: 508-255-8292 | | | | | |
| Contractor Email: pineknoll123@gmail.com | | | | | |
| Reason/explanation: New Construction | | | | | |
| I/we hereby agree to the terms and conditions as outlined in this policy and attached Exhibits: | | | | | |
| Applicant's Signature: 4/7/22 | | | | | |
| Owner's Signature (if different): | | | | | |



TOWN OF TRURO

P.O. Box 2030, Truro MA 02666
Tel: (508) 349-7004 Fax: (508) 349-5505

POLICY MEMORANDUM #28

Date: Adopted June 6, 2000, revised 9/22/04, 2/28/06, 6/13/06, 10/13/07

Subject: CURB CUT POLICY

1. Introduction

Due to the continuing growth in construction activity in Truro and the associated growth in curb cuts, the Board of Selectmen has established the following Curb Cut Policy in order to address inherent safety concerns.

This policy is intended to provide control over access to Town or State owned roads and uniformity of requirements and standards of construction for every curb cut request. Upon inspection by the Director of the Department of Public Works, there may be additional construction requirements imposed for a particular situation, but none that would be contradictory to the Subdivision Control Laws as outlined in MGL Chapter 41, Sections 81K through 81GG, or the Town of Truro Rules and Regulations governing the Subdivision of Land (Rules and Regulations), Sections 3.6.2, 3.6.6, 4, Table 1 and Section 1.5.

2. Policy

Alteration of existing curb cut(s) and/or requests for additional curb cuts off of a Town or State owned road(s) shall cause an applicant to for file a Curb Cut Permit (CCP). Any application for a building permit that includes a proposed curb cut on property off a Town or State owned road will first require an approved CCP. The approved CCP must be provided to the Truro Building Commissioner prior to or at the time of requesting a building permit. No such building permit will be issued without an approved CCP. Additionally, a final certificate of occupancy for the construction will not be issued unless the conditions of the CCP have been met.

The Truro Board of Selectmen will refer any Town concerns regarding proposed curb cuts on State owned roads to the Massachusetts Highway Department for consideration.

The curb cut construction requirements of this Policy will be applicable to new construction, existing structures, and renovations thereto.

3. Action

Application for a CCP will be made on approved forms available at Town Hall or the Department of Public Works. A copy of the current (as of this date) CCP application form is attached as Exhibit 1. The applicant for

Selectmen's Policy #28 Curb Cut Policy Page 2

a CCP, or his/her agent, will be available to the Director of the Department of Public Works and the Chief of Police to enable a site inspection and to answer any questions regarding the CCP application.

The Planning Board approval/sign off is required for approved subdivision roads on Town or State roads and for endorsed Site Plan Review on Town or State roads.

All curb cuts shall be located and constructed in such a manner so as to **preclude**:

- a. Damage to the Town or State road either at the time of construction or in the future;
- b. Drainage from private property onto the Town or State road;
- c. Introduction of sand, soils, or other materials onto the Town or State road; and
- d. Any other potential hazard to public safety as may be identified by the Director of the Department of Public Works and/or the Chief of Police.

All curb cuts will comply with the Town of Truro construction requirements, as noted on the attached information sheet and shown as Exhibit 2; the design standards shown under the Rules and Regulations, Section 2.5.8; the Mass Highway permit requirements as applicable; and/or as required by the Director of the Department of Public Works.

All applications for a curb cut and approval of performance conditions on Town roads shall be subject to review, including a site visit by the Director of the Department of Public Works and the Chief of Police, prior to approval. The Director shall make recommendations on each application, based upon the Town's construction requirements as outlined above, such as location, materials to be used, catch basin(s) location(s), and so forth, if required. All such required construction will be at the applicant's expense. The Chief of Police will review the application site to ascertain that the curb cut will not be detrimental to traffic flow and the public's safety.

Final approval by the Director of the Department of Public Works shall be made only after approval by the Planning Board, if required, after completion of all construction, and after a final inspection by the Director of the Department of Public Works has been made. Final written approval shall become a part of the property records maintained by the Building Commissioner, and shall be completed prior to the issuance of a certificate of occupancy.

The Board of Selectmen may waive any requirements of this policy, at their sole discretion, when such waiver is deemed to be in the best interests of, and at no cost to, the Town of Truro.

4. Enforcement

Failure to comply with this policy shall result in one or more of the following actions:

a. A refusal to issue a building permit (permit approval) and/or a certificate of occupancy (permit compliance);

Selectmen's Policy #28 Curb Cut Policy Page 3

- b. A request to Mass Highway for disapproval of the applicant's request for a permit to enter a State Highway; and/or
- c. A penalty of \$300.00 for each violation through the non-criminal disposition process as outlined in the Truro General Bylaws. Each day a violation exists shall be considered a new violation.

2. Process

Following is an outline of the chronological process to be used for conformance to this Policy:

- a. Applicant submits an approved application for a Curb Cut Permit.
- b. Director of the Department of Public Works performs a site visit, attaches his recommendations to the Board of Selectmen, and forwards the completed curb cut application to the Chief of Police.
- c. The Chief of Police performs a site visit; he notes his approval/disapproval of the application based on safety considerations and forwards the application to the Board of Selectmen.
- d. Board of Selectmen approves/disapproves the application w/wo conditions and forwards the results to the applicant. If the application is disapproved, the process starts over again with a revised application reflecting the reason(s) for disapproval.
- e. Upon the approval of the Board of Selectmen, applicants whose curb cut applications are tied to a building permit will proceed as below:
 - 1. Applicant includes the approved Curb Cut Permit to his/her application for a building permit.
 - 2. Construction occurs.
 - 3. Property owner or his/her agent applies for a certificate of occupancy.
 - 4. Director of the Department of Public Works performs a site visit to determine compliance with the conditions of the Curb Cut Permit and informs the Building Commissioner, in writing, that the conditions have or have not been met. If the latter, the applicant will be informed of what actions are required to meet the conditions of the Curb Cut Permit and that they must be completed prior to the issuance of a certificate of occupancy.

| Alfred Gaechter, Chairman | Gary Palmer, Vice-Chairman | |
|----------------------------|---|--|
| Christopher R. Lucy, Clerk | Curtis Hartman | |
| _ | Janet W. Worthington Board of Selectmen | |
| | Town of Truro | |

EXHIBIT 2

TOWN OF TRURO CURB CUT DESIGN AND CONSTRUCTION REQUIREMENTS

<u>General:</u> Any owner of property abutting Town or State roads shall, before beginning any construction, make written application to the Board of Selectmen, in duplicate. The application will be accompanied by a plan showing the following:

- 1. Complete plans drawn to scale on the property in question, including the location of property lines and all existing driveways, using a scale of no less than 40' = 1''.
- 2. Indication of any drive that is to be altered or closed.

The following additional requirements must be met and agreed upon by the applicant/owner:

- 1. The applicant must furnish a list of all materials, including any necessary signs, to be part of any construction within the Town or State layout.
- 2. All work and material shall meet the standards of the Town of Truro and/or the Mass Highway requirements, if applicable.
- 3. Any alterations to the original application shall require a new permit.
- 4. All curb cuts and street approaches will be inspected during and after construction, and the Town has the right to stop work until such time as any objectionable conditions are corrected at the applicant/owner's expense.
- 5. The cost of any/all construction and maintenance of any work to take place within the Town or State layout; all materials and labor; and any work specified and approved by the Board of Selectmen, shall be borne by the applicant/owner, their grantees, successors and assignees.


Design and Construction Requirements:


Driveways should be located to the best advantage with regard to the road alignment, profile, sight distance conditions, road safety, and so forth.


The standards call for not more than one (1) curb cut for any one property. A variance may be granted by the Board of Selectmen, subject to an individual need.


The radius of a private driveway may not extend beyond the private owner's property line without the abutting owner's written consent.

All driveways or private road entrances or exits shall be hot mixed and bermed, oiled, or hardened with such materials to the road/property sideline so as to prevent erosion of such driveway/private road entrance or exit which would cause sand or material to be washed onto Town or State roads. This should be completed as soon as possible, weather permitting.









GENERAL NOTES:

A.) NEITHER DRIVEWAYS NOR PARKING AREAS ARE ALLOWED OVER SEPTIC SYSTEM LINLESS H-20 COMPONENTS ARE USED.

B.) THE DESIGNER WILL NOT BE RESPONSIBLE FOR THE SYSTEM AS DESIGNED UN-LESS CONSTRUCTED AS SHOWN. ANY CHANGES SHALL BE APPROVED IN WRITING.

C.) CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THE LOCATION OF ALL UNDERGROUND AND OVERHEAD UTILITIES PRIOR TO COMMENCEMENT OF WORK.

CONSTRUCTION NOTES:

- 1.) ALL CONSTRUCTION SHALL CONFORM TO THE STATE ENVIRONMENTAL CODE, TITLE 5. AND THE REQUIREMENTS OF THE LOCAL BOARD OF HEALTH.
- 2.) SEPTIC TANK(S), GREASE TRAP(S), DOSING CHAMBER(S) AND DISTRIBUTION BOX(ES) SHALL BE SET ON A LEVEL STABLE BASE WHICH HAS BEEN MECHANICALLY COMPACTED, OR ON A 6 INCH CRUSHED STONE BASE.
- 3.) SEPTIC TANK(S) SHALL MEET ASTM STANDARD C1127-93 AND SHALL HAVE AT LEAST THREE 20" DIAMETER MANHOLES. THE MINIMUM DEPTH FROM THE BOT-TOM OF THE SEPTIC TANK TO THE FLOW LINE SHALL BE 48".
- 4.) SCHEDULE 40 PVC INLET AND OUTLET TEES SHALL EXTEND A MINIMUM OF 6" ABOVE THE FLOW LINE OF THE SEPTIC TANK AND SHALL BE INSTALLED ON THE CENTERLINE OF THE TANK DIRECTLY UNDER THE CLEANOUT MANHOLE.
- 5.) RAISE COVERS OF THE SEPTIC TANK AND DISTRIBUTION BOX WITH PRECAST CONCRETE WATER TIGHT RISERS OVER INLET AND OUTLET TEES TO WITHIN 6" OF FINISH GRADE, OR AS APPROVED BY THE LOCAL BOARD OF HEALTH AGENT.
- 6.) PIPING SHALL CONSIST OF 4" SCHEDULE 40 PVC OR EQUIVALENT. PIPE SHALL BE LAID ON A MINIMUM CONTINUOUS GRADE OF NOT LESS THAN 1%.
- 7.) DISTRIBUTION LINES FOR SOIL ABSORPTION SYSTEM (AS REQUIRED) SHALL BE 4" DIAMETER SCHEDULE 40 PVC LAID AT 0.005 FT/FT. LINE SHALL BE CAPPED
- 8.) OUTLET PIPES FROM DISTRIBUTION BOX SHALL REMAIN LEVEL FOR AT LEAST 2' BEFORE PITCHING TO SOIL ABSORPTION SYSTEM. WATER TEST DISTRIBUTION BOX TO ASSURE EVEN DISTRIBUTION.
- 9.) DISTRIBUTION BOX SHALL HAVE A MINIMUM SUMP OF 6" MEASURED BELOW THE OUTLET INVERT.
- 10.) BASE AGGREGATE FOR THE LEACHING FACILITY SHALL CONSIST OF 3/4" TO 1-1/2" DOUBLE WASHED STONE FREE OF IRON, FINES AND DUST AND SHALL BE INSTALLED BELOW THE CROWN OF THE DISTRIBUTION LINE TO THE BOTTOM OF THE SOIL ABSORPTION SYSTEM. BASE AGGREGATE SHALL BE COVERED WITH A 2" LAYER OF 1/8" TO 1/2" DOUBLE WASHED STONE FREE OF IRON, FINES AND DUST.
- 11.) VENT SOIL ABSORPTION SYSTEM WHEN DISTRIBUTION LINES EXCEED 50 FEET: WHEN LOCATED EITHER IN WHOLE OR IN PART UNDER DRIVEWAYS, PARKING AREAS, TURNING AREAS OR OTHER IMPERVIOUS MATERIAL; OR WHEN PRESSURE DOSED.
- 12.) SOIL ABSORPTION SYSTEM SHALL BE COVERED WITH A MINIMUM OF 9" OF CLEAN MEDIUM SAND (EXCLUDING TOPSOIL).
- 13.) FINISH GRADE SHALL BE A MAXIMUM OF 36" OVER THE TOP OF ALL SYSTEM COMPONENTS, INCLUDING THE SEPTIC TANK, DISTRIBUTION BOX, DOSING CHAMBER AND SOIL ABSORPTION SYSTEM. SEPTIC TANKS SHALL HAVE A MINIMUM COVER
- 14.) FROM THE DATE OF INSTALLATION OF THE SOIL ABSORPTION SYSTEM UNTIL RECEIPT OF A CERTIFICATE OF COMPLIANCE, THE PERIMETER OF THE SOIL ABSORP TION SYSTEM SHALL BE STAKED AND FLAGGED TO PREVENT THE USE OF SUCH AREA FOR ALL ACTIVITIES THAT MIGHT DAMAGE THE SYSTEM.
- 15.) EXISTING CESSPOOL(S) TO BE REMOVED OR ABANDONED IN PLACE IN ACCORDANCE WITH 310 CMR 15.354. CESSPOOL AND ANY CONTAMINATED SOIL WITHIN 5' OF THE PROPOSED SOIL ABSORPTION SYSTEM SHALL BE REMOVED AND REPLACED WITH CLEAN SAND. AREA TO BE COMPACTED TO MINIMIZE SETTLING.
- 16.) INSTALLER SHALL VERIFY BUILDING SEWER INVERT ELEVATION PRIOR TO INSTALLATION OF ANY SEPTIC SYSTEM COMPONENTS.

SYSTEM DESIGN CALCULATIONS:

SEWAGE DESIGN FLOW: 5 BEDROOM DWELLING @ 110 GPD = 550 GPD

LEACHING CAPACITY REQUIRED

5 BEDROOMS (MAX.) @ 110 GPD = 550 GPD REQUIRED

SEPTIC TANK CAPACITY REQUIRED: DAILY FLOW = 550 GPD @ 200% = 1,100 GAL. REQUIRED

SEPTIC TANK CAPACITY PROVIDED:

1500 GALLON SEPTIC TANK (MIN. ALLOWED)

ONE (1) 42.0" X 12.83" X 2.0" LEACHING CHAMBER CAN LEACH: Vt=[(42.0 X 12.83) + (42.0 X 2.0)2 + (12.83 X 2.0)2] X 0.74 GPD/SF=561.05 GPD 561 GPD>550 GPD REQUIRED

NOTE: A GARBAGE DISPOSAL IS NOT PERMITTED WITH THIS DESIGN.

ONE (1)- 1500 GALLON SEPTIC TANK
ONE (1)- 6 OUTLET DISTRIBUTION BOX (H-20 RATED)

FOUR (4) - 500 GALLON LEACH CHAMBERS WITH 4' OF STONE ALL AROUND

SOIL TEST LOGS:

| DEPTH FROM SURFACE (INCHES) | SOIL HORIZON | SOIL TEXTURE (USDA) | SOIL COLOR (MUNSELL) | MOTTLING | OTHER |
|-----------------------------------|-----------------|---------------------------|----------------------------|----------|-----------------------|
| 0-9 | Α | Loamy Sand | 10YR3/2 | NONE | |
| 9-21 | В | Loamy Sand | 10YR7/6 | NONE | |
| 21-156 | C1 | Medium-Coarse Sand | 10YR6/4 | NONE | PERC @ 39"; <2 MIN/IN |

TEST HOLE 2: EL=110,4±

| DEPTH FROM SURFACE (INCHES) | | SOIL TEXTURE (USDA) | | MOTTLING | OTHER |
|-----------------------------------|----|---------------------------|---------|----------|-------|
| 0-10 | Α | Loamy Sand | 10YR3/2 | NONE | |
| 10-28 | В | Loamy Sand | 10YR7/6 | NONE | |
| 28-120 | C1 | Medium-Coarse Sand | 10YR6/4 | NONE | |

DATE OF TESTING: 11/30/2021

PERCOLATION RATE: LESS THAN 2 MIN/INCH IN 'C1' LAYER.
WITNESSED BY: ROBERT REEDY, P.E., J.M. O'REILLY & ASSOCIATES, INC.

AROZANA DAVIS, TRURO HEALTH DEPARTMENT

NO WATER ENCOUNTERED

USE A LOADING RATE OF 0.74 GPD/SF FOR SIZING OF SOIL ABSORPTION SYSTEM.

TEST HOLE 3: EL=109.2±


| DEPTH FROM SURFACE (INCHES) | SOIL HORIZON | SOIL TEXTURE (USDA) | SOIL COLOR (MUNSELL) | MOTTLING | OTHER |
|-----------------------------------|-----------------|---------------------------|----------------------------|----------|-----------------------|
| 0-10 | Α | Loamy Sand | 10YR3/2 | NONE | |
| 10-28 | В | Loamy Sand | 10YR7/6 | NONE | |
| 28-127 | C1 | Medium-Coarse Sand | 10YR6/4 | NONE | PERC @ 46"; <2 MIN/IN |

TEST HOLE 4: EL=108,6±

| DEPTH FROM SURFACE (INCHES) | SOIL HORIZON | SOIL TEXTURE (USDA) | | MOTTLING | OTHER |
|-----------------------------------|-----------------|---------------------------|---------|----------|-------|
| 0-9 | Α | Loamy Sand | 10YR3/2 | NONE | |
| 9-24 | В | Loamy Sand | 10YR7/6 | NONE | |
| 24-160 | C1 | Medium-Coarse Sand | 10YR6/4 | NONE | |


FLOW PROFILE:

NOT TO SCALE



INSPECTION NOTE:

PRIOR TO FINAL INSPECTION BY THE ENGINEER, SYSTEM NEEDS TO BE COMPLETE INCLUDING BUILDUP FOR COVERS.



SHEET 2 OF 2

Amy Holt

c/o Pine Knoll Builders, P.O. Box 1347, N. Eastham, MA 02651

SEWAGE DISPOSAL SYSTEM DESIGN & NOTES Lot 4, 105 Castle Road, Truro, MA



TH OF M

JOHN M.

O'REILLY

CIVIL NO. 36200

J.M. O'REILLY & ASSOCIATES, INC.


Professional Engineering & Land Surveying Services


1573 Main Street - Route 6A

P.O. Box 1773 (508)896-6601 Office Brewster, MA 02631 (508)896-8602 Fax

JOB NUMBER: JMO JMO-9171 As Noted 01/25/2022

G.\AAlobs\Pine Knoll Builders\9225- Lot 4 105 Castle Rd Truro\dwg\9225.SDS PLAN.dwg





Pine Knoll 508-255-8292 3 Main Street, Unit 25 N. Eastham, MA 02651

To Whom it may concern,

For the new construction at 113 Castle Rd, Truro, it was realized through the collection of the asbuilt data that the dwelling exceeds Truro's maximum height restrictions by 1'-6". In order to correct this conflict, the truss system has to be adjusted so that the ridge height is lowered by at least 1'-6". Within this packet is the engineered stamped truss adjustments lowering the ridge height by 1'-9". This will put the new height 3" below Truro's maximum height.

It is the intent of the homeowner and the general contractor to complete this correction as soon as possible. Due to the availability of labor, this work cannot be done before the summer, so the intent is to complete this correction by the end of the year 2024.

The original intent was for the house to be ready for move-in by this summer. Since the corrective work will delay the final CO until after summer, it is the general contractor's intent to complete all work except for final energy sign off and the final CO and receive a partial CO so that the homeowner can be in the house for the summer. Once summer is over and the house is empty, the corrective work would take place before the end of the year.

Amy Holt (Honfe owner)

Paul Holt (Home owner)

John Ferro (General Contractor)

4/23/24

Commonwealth of Massachusetts

Country of Bainstable

Commonwealth of Masser Tell, Paul, Holt, and on 4/23/24 before me the undersigned Army Holt, Paul, Holt, and John Ferro proved to me by Ma beense swere to me that they signed the document as their free act and deed.


Kaser a. La Voie Comm: 12/29/28 Karen a. La Voie Comm: 12/29/28

| Job | Truss | Truss Type | Qty | Ply | 105 Castle Rd |
|--------|-------|------------|-----|-----|--------------------------|
| Q15203 | Т3 | Common | 6 | 1 | Job Reference (optional) |

Run: 8.53 S May 4 2022 Print: 8.530 S May 4 2022 MiTek Industries, Inc. Thu Jul 21 14:52:50

 $ID: GG1Z2dJD5mJWpbKpN24AoazYR89-ORw7mj7CIDjxbNEeuavOrMHdG_yUUh_yAkw3jXyvq3x$

Page: 1



Scale = 1:70.2

Plate Offsets (X, Y): [2:0-3-14,Edge], [3:0-1-12,0-2-8], [4:0-6-0,0-3-4], [6:0-6-0,0-3-4], [7:0-1-12,0-2-8], [8:0-3-14,Edge], [10:0-3-8,0-2-12], [13:0-2-0,0-1-12], [14:0-2-0,0-1-12], [17:0-3-8,0-2-12]

| | | | _ | | | | | | | | | _ |
|-------------|-------|-----------------|-----------------|------------|------|----------|-------|-------|--------|-----|----------------|----------|
| Loading | (psf) | Spacing | 2-0-0 | CSI | | DEFL | in | (loc) | I/defl | L/d | PLATES | GRIP |
| TCLL (roof) | 30.0 | Plate Grip DOL | 1.15 | TC | 0.93 | Vert(LL) | -0.30 | 14-16 | >999 | 360 | MT20 | 197/144 |
| Snow (Pf) | 35.0 | Lumber DOL | 1.15 | BC | 0.99 | Vert(CT) | -0.51 | 11-13 | >938 | 240 | MT18HS | 197/144 |
| TCDL | 15.0 | Rep Stress Incr | YES | WB | 0.93 | Horz(CT) | 0.20 | 10 | n/a | n/a | | |
| BCLL | 0.0* | Code | IRC2015/TPI2014 | Matrix-MSH | | | | | | | | |
| BCDL | 10.0 | | | | | | | | | | Weight: 186 lb | FT = 20% |

LUMBER

TOP CHORD 2x4 SPF 2100F 1.8E *Except* T1:2x4 SPF 1650F 1.5E BOT CHORD 2x4 SPF No.2 *Except* B2:2x4 SPF 1650F 1.5E WEBS 2x4 SPF No.2 *Except* W1:2x6 SPF 1650F 1.5E

REACTIONS (lb/size) 10=2515/0-5-8, (min. 0-3-15), 17=2515/0-5-8, (min. 0-3-15)

Max Horiz 17=158 (LC 20)

Max Uplift 10=-328 (LC 17), 17=-328 (LC 16)

BRACING

TOP CHORD BOT CHORD

WEBS

Structural wood sheathing directly applied, except end verticals. Rigid ceiling directly applied or 2-2-0 oc bracing, Except: 10-0-0 oc bracing: 13-14.

10-0-0 oc bracing: 13-1 1 Row at midpt

6-13, 4-14, 3-17, 7-10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-18=-856/220, 3-18=-705/239, 3-4=-3886/558, 4-19=-3233/511, 5-19=-3081/531, 5-20=-3081/531, 6-20=-3233/511,

 $6\text{-}7\text{=-}3886/558, \, 7\text{-}21\text{=-}705/238, \, 8\text{-}21\text{=-}856/220, \, 2\text{-}17\text{=-}779/276, \, 8\text{-}10\text{=-}779/276}$

16-17=-518/3499, 16-22=-359/3123, 15-22=-359/3123, 15-23=-359/3123, 14-23=-359/3123, 14-24=-145/2408, 24-25=-145/2408, 13-25=-145/2408, 13-26=-231/3123, 12-26=-231/3123, 12-27=-231/3123, 11-27=-231/3123, 12-26=-231/3123, 12-27=

10-11=-360/3499

5-13=-240/1230, 6-13=-1053/340, 6-11=-133/513, 7-11=-270/223, 5-14=-240/1230, 4-14=-1053/340, 4-16=-133/513,

3-16=-270/223, 3-17=-3316/283, 7-10=-3316/283


WEBS NOTES

BOT CHORD

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-10; Vult=140mph (3-second gust) Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; BCDL=6.0psf; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior (2) -1-0-0 to 3-0-6, Interior (1) 3-0-6 to 20-2-0, Exterior (2) 20-2-0 to 24-2-6, Interior (1) 24-2-6 to 41-4-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pf=35.0 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 35.0 psf on overhangs non-concurrent with other live loads.
- 6) All plates are MT20 plates unless otherwise indicated.
- 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 328 lb uplift at joint 17 and 328 lb uplift at joint 10.
- 0) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



TOP CHORD BOT CHORD

WEBS

LUMBER-

TOP CHORD 2x4 SPF 2100F 1.8E *Except*

T1: 2x4 SPF No.2 BOT CHORD 2x4 SPF 1650F 1.5E

2x4 SPF No.2 *Except* **WEBS**

W1: 2x6 SPF 1650F 1.5E

REACTIONS. (lb/size) 16=2393/0-5-8 (min. 0-3-12), 10=2392/0-5-8 (min. 0-3-12)

Max Horz 16=147(LC 20)

Max Uplift 16=-295(LC 16), 10=-295(LC 17)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

1-17=-677/130, 2-17=-509/149, 2-3=-3793/486, 3-4=-3541/516, 4-18=-2832/455, TOP CHORD

5-18=-2681/475, 5-19=-2681/475, 6-19=-2832/455, 6-7=-3541/516, 7-8=-3793/486,

8-20=-509/149, 9-20=-677/131, 1-16=-546/166, 9-10=-546/166

15-16=-549/3518, 15-21=-369/3125, 14-21=-369/3125, 14-22=-369/3125, BOT CHORD 13-22=-369/3125, 13-23=-276/3125, 12-23=-276/3125, 12-24=-276/3125,

11-24=-276/3125, 10-11=-404/3518

2-16=-3499/401, 8-10=-3499/401, 4-15=-51/489, 2-15=-313/236, 4-13=-1171/326, **WEBS**

5-13=-194/1635, 6-13=-1171/326, 6-11=-51/489, 8-11=-313/236

NOTES-

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) 0-2-12 to 4-3-2, Interior(1) 4-3-2 to 20-2-0, Exterior(2) 20-2-0 to 24-2-6, Interior(1) 24-2-6 to 40-1-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pf=35.0 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) All plates are MT20 plates unless otherwise indicated.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 295 lb uplift at joint 16 and 295 lb uplift at joint
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



Structural wood sheathing directly applied, except end verticals.

installed during truss erection, in accordance with Stabilizer

2-16, 8-10, 4-13, 6-13

MiTek recommends that Stabilizers and required cross bracing be

Rigid ceiling directly applied or 2-2-0 oc bracing.

1 Row at midpt


Installation guide

03/12/2024

| Job | | Truss | Truss Type | Qty | Ply | 105 Castle Rd |
|--------|---|-------|------------------------|-----|-----|--------------------------|
| Q15203 | 3 | T2GE | Common Supported Gable | 1 | 1 | Job Reference (optional) |

Run: 8.53 S Jan 25 2022 Print: 8.530 S May 4 2022 MiTek Industries, Inc. Thu Jul 21 14:52:49

ID:KcON374IZwwD1gNAmZFjXazYR8S-wFNIYN6aXvb5 DfSKtO9J9kf7bqSlNyox4BWB5yvq3y



Scale = 1:67.6

| Loading | (psf) | Spacing | 2-0-0 | CSI | | DEFL | in | (loc) | l/defl | L/d | PLATES | GRIP |
|-------------|-------|-----------------|-----------------|-----------|------|-----------|------|-------|--------|-----|----------------|----------|
| TCLL (roof) | 30.0 | Plate Grip DOL | 1.15 | TC | 0.12 | Vert(LL) | n/a | - | n/a | 999 | MT20 | 197/144 |
| Snow (Pf) | 35.0 | Lumber DOL | 1.15 | BC | 0.08 | Vert(TL) | n/a | - | n/a | 999 | | |
| TCDL | 15.0 | Rep Stress Incr | YES | WB | 0.34 | Horiz(TL) | 0.01 | 24 | n/a | n/a | | |
| BCLL | 0.0* | Code | IRC2015/TPI2014 | Matrix-MR | | | | | | | | |
| BCDL | 10.0 | [| | | | | | | | | Weight: 213 lb | FT = 20% |

LUMBER TOP CHORD 2x4 SPF No.2 **BOT CHORD** 2x4 SPF No.2 WEBS 2x4 SPF No.2 **OTHERS** 2x4 SPF No.2

REACTIONS All bearings 40-4-0.

(lb) - Max Horiz 46=149 (LC 20)

Max Uplift All uplift 100 (lb) or less at joint(s) 24, 26, 27, 28, 29, 30, 31, 33, 34, 36, 37, 39, 40, 41, 42, 43, 44, 46 except 25=-197 (LC 17), 45=-153 (LC 16)

Max Grav All reactions 250 (lb) or less at joint(s) 24, 27, 28, 29, 30, 40, 41, 42, 43, 44, 46 except 25=309 (LC 23), 26=325 (LC 1), 31=312 (LC 23), 33=333 (LC 23), 34=350 (LC 23), 35=256 (LC 28), 36=350 (LC 22), 37=333 (LC 22), 39=312 (LC 22), 45=265 (LC 1)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 6-7=-91/258, 7-47=-109/303, 8-47=-86/308, 8-9=-126/349, 9-10=-113/358, 10-11=-144/411, 11-12=-161/453,

12-13=-161/444, 13-14=-144/401, 14-15=-113/348, 15-16=-126/339, 16-48=-86/299, 17-48=-109/294 **WEBS** 22-25=-262/257, 12-35=-253/29, 11-36=-309/159, 10-37=-292/138, 8-39=-271/94, 13-34=-309/158, 14-33=-292/138,

16-31=-271/94, 21-26=-270/187

NOTES

Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-10; Vult=140mph (3-second gust) Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Corner (3) 0-1-12 to 4-2-0, Exterior (2) 4-2-0 to 20-2-0, Corner (3) 20-2-0 to 24-2-0, Exterior (2) 24-2-0 to 40-2-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pf=35.0 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; 4) Partially Exp.; Ct=1.10
- 5) Unbalanced snow loads have been considered for this design.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- 8) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc. 9)
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads. 10)
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and 11) any other members
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 46, 24, 36, 37, 39, 40, 41, 42, 43, 44, 34, 33, 31, 30, 29, 28, 27, 26 except (jt=lb) 25=196, 45=152.

BRACING

BOT CHORD

WEBS

TOP CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.

Rigid ceiling directly applied or 10-0-0 oc bracing 12-35, 11-36, 13-34 1 Row at midpt

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

Job Truss Truss Type Qty 105 Castle Rd [PRELIM] Q15203 A01GE Common Supported Gable Job Reference (optional) R630 s May 25 2023 MTRel Industries, Inc. Mon Mar 11 17:32:15 2024 Page 1 ID:KcON374IZwwD1gNAmZFjXazYR8S-7nvGAMzv2XG6_FeTvCHYwot7r_7MMt6IQJSvsEzbxQE 20-2-0 40-4-0 20-2-0 Repair to Shorten Truss 1-9-0 Scale = 1:72.1 5x5 =5.50 12 Add 2x4 #2 SPF As Shown 4-3-8 13 4-9-4 4-9-4 Attach 7/16" 24/16 APA Sheathing To Both Sides With (2) Rows 0.131 x 2-3/8" Nails at 10 T2 3x6 < 3x6 = 15 3" c/c Into All Members As Shown 48 16 17 6 Š 10-2-15 19 10 20 21 SIT5 ST122 4x5 > 4x5 / **S**T SIT4 SITI3 0-0-31 30 38 |46 44 37 36 35 34 33 28 45 42 41 40 32 29 26 25 39 2x4 | | 3x4 =3x4 = 2x4 | II3x6 =3x6 _ 13-6-8 13-6-8 40-4-0 40-4-0 Plate Offsets (X,Y)-- [1:0-1-12,0-2-0], [23:0-1-12,0-2-0], [31:0-2-4,0-1-8], [39:0-2-4,0-1-8] LOADING (psf) SPACING-2-0-0 CSI. DEFL. I/defl L/d **PLATES GRIP** in (loc) TCLL (roof) 30.0 Plate Grip DOL TC 1.15 0.09 Vert(LL) 999 197/144 MT20 n/a n/a Snow (Pf) 35.0 Lumber DOL ВС 0.03 Vert(CT) 999 1.15 n/a n/a **TCDL** 15.0 WB Rep Stress Inci YES 0.34 Horz(CT) 0.01 25 n/a n/a **BCLL** 0.0 Ode IRC2015/TPI2014 FT = 20%

LUMBER-

BCDI

TOP CHORD 2x4 SPF No.2 BOT CHORD 2x4 SPF No.2

10.0

2x6 SPF 1650F 1.5E *Except* **WEBS**

W2: 2x4 SPF No.2

OTHERS 2x4 SPF No.2

BRACING-TOP CHORD

Matrix-SH

BOT CHORD

WFBS

Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals

Weight: 219 lb

Rigid ceiling directly applied or 10-0-0 oc bracing. 1 Row at midpt 12-35, 11-36, 13-34

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide

REACTIONS. All bearings 40-4-0.

Max Horz 46=147(LC 16)

Max Uplift All uplift 100 lb or less at joint(s) 46, 36, 37, 38, 40, 41, 42, 43, 44, 34, 33, 32, 30, 29, 28, 27, 26 except 45=-155(LC 16), 25=-132(LC 17) Max Grav All reactions 250 lb or less at joint(s) 46, 24, 35, 40, 41, 42, 43, 44, 30, 29, 28, 27, 26 except 36=349(LC 22), 37=332(LC 22), 38=311(LC 22), 45=254(LC 22), 34=349(LC 23), 33=332(LC 23), 32=311(LC 23), 25=254(LC 23)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

9-10=-103/272, 10-11=-121/324, 11-12=-138/368, 12-13=-138/357, 13-14=-121/307, TOP CHORD

14-15=-103/255

WEBS 11-36=-309/163, 10-37=-292/136, 9-38=-271/95, 13-34=-309/162, 14-33=-292/136,

15-32=-271/95

NOTES-

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) 0-2-12 to 4-2-0, Exterior(2) 4-2-0 to 20-2-0, Corner(3) 20-2-0 to 24-2-0, Exterior(2) 24-2-0 to 40-1-4 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pf=35.0 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 5) Unbalanced snow loads have been considered for this design.
- 6) All plates are 1.5x4 MT20 unless otherwise indicated.
- 7) Gable requires continuous bottom chord bearing.
- 8) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- 9) Gable studs spaced at 2-0-0 oc.
- 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 46, 36, 37, 38, 40, 41, 42, 43, 44, 34, 33, 32, 30, 29, 28, 27, 26 except (jt=lb) 45=155, 25=132.
- 13) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced Continuedand AAGH/27PI 1.



03/12/2024 2 of 4

| Job | Truss | Truss Type | Qty | Ply | 105 Castle Rd |
|--------|-------|-------------------------|-----|-----|--------------------------|
| Q15203 | T1 | Common Structural Gable | 1 | 1 | Job Reference (optional) |

Run: 8.53 S May 4 2022 Print: 8.530 S May 4 2022 MiTek Industries, Inc. Thu Jul 21 14:52:47

ID:ke0fYXirtP0cpvWCSYBSm1zYR8x-WghcwL4hE_DW7mwtfkqShW6ybNeDYw0MF6ysbmyvq4?

Structural wood sheathing directly applied or 3-9-7 oc purlins,

MiTek recommends that Stabilizers and required cross bracing be

installed during truss erection, in accordance with Stabilizer


Rigid ceiling directly applied or 6-0-0 oc bracing.

except end verticals.

Installation guide.

61.62

1 Brace at Jt(s): 47, 48, 49, 50, 51, 53, 54, 55, 56, 57, 58, 59,



Scale = 1:70.2

[2:0-3-14, Edge], [7:0-2-8,0-3-0], [15:0-2-8,0-3-0], [20:0-3-14, Edge], [22:0-2-4,0-2-8], [26:0-5-0,0-2-4], [30:0-1-12,0-1-8], [37:0-1-12,0-1-8], [41:0-5-0,0-2-4], [41:0-5Plate Offsets (X, Y): [43:0-3-4,0-1-8], [46:0-2-4,0-2-8]

| | / 6 | | | | | | | <i>(</i> 1) | | | | |
|-------------|-------|-----------------|-----------------|------------|------|----------|-------|--------------|--------|-----|----------------|----------|
| Loading | (psf) | Spacing | 2-0-0 | CSI | | DEFL | ın | (loc) | l/defl | L/d | PLATES | GRIP |
| TCLL (roof) | 30.0 | Plate Grip DOL | 1.15 | TC | 0.84 | Vert(LL) | -0.12 | 27-28 | >999 | 360 | MT20 | 197/144 |
| Snow (Pf) | 35.0 | Lumber DOL | 1.15 | BC | 0.82 | Vert(CT) | -0.20 | 27-28 | >999 | 240 | MT18HS | 197/144 |
| TCDL | 15.0 | Rep Stress Incr | YES | WB | 0.80 | Horz(CT) | 0.03 | 22 | n/a | n/a | | |
| BCLL | 0.0* | Code | IRC2015/TPI2014 | Matrix-MSH | | | | | | | | |
| BCDL | 10.0 | | | | | | | | | | Weight: 297 lb | FT = 20% |

BOT CHORD

JOINTS

LUMBER **BRACING** TOP CHORD 2x4 SPF No.2 TOP CHORD

BOT CHORD 2x4 SPF No.2 2x4 SPF No.2 *Except* W1:2x6 SPF 1650F 1.5E **WEBS**

OTHERS 2x4 SPF No.2

REACTIONS All bearings 15-5-8. except 22=0-5-8

(lb) - Max Horiz 46=-157 (LC 21)

Max Uplift All uplift 100 (lb) or less at joint(s) 38, 39, 40, 42, 45 except 22=-249 (LC 17), 37=-229 (LC 17), 41=-180 (LC 16), 46=-110

Max Grav All reactions 250 (lb) or less at joint(s) 38, 39, 42, 44, 45 except 22=1482 (LC 24), 37=2540 (LC 1), 40=287 (LC 1), 41=343 (LC

23), 46=467 (LC 23)

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-63=-471/209, 3-63=-331/228, 3-4=-2/271, 4-5=0/339, 5-6=0/328, 6-64=0/320, 7-64=0/327, 7-8=0/749, 8-9=0/769,

9-10=0/739, 10-11=0/793, 11-12=-983/397, 12-13=-1073/368, 13-14=-1063/324, 14-15=-1029/294, 15-16=-1741/467, 16-17=-1805/443, 17-18=-1829/403, 18-19=-1851/394, 19-65=-863/234, 20-65=-1016/215, 2-46=-597/274,

20-22=-850/266

40-41=-588/234, 39-40=-588/234, 38-39=-588/234, 37-38=-588/234, 29-30=-26/1095, 28-29=-26/1095, 27-28=-26/1095,

26-27=-26/1095, 25-26=-220/1702, 24-25=-220/1702, 23-24=-220/1702, 22-23=-220/1702

11-55=-326/1479, 55-56=-331/1489, 30-56=-343/1548, 30-57=-794/219, 15-57=-758/210, 15-58=-244/914,

58-59=-227/840, 26-59=-220/824, 19-26=-298/161, 37-48=-2114/171, 47-48=-2003/159, 11-47=-2125/172, 7-49=-315/62, 37-49=-340/68, 41-51=-70/494, 50-51=-70/489, 7-50=-75/527, 3-41=-703/318, 46-54=-194/343, 53-54=-192/339,

52-53=-196/347, 3-52=-231/409, 19-60=-1070/153, 60-61=-1071/115, 61-62=-1057/113, 22-62=-1038/113,

11-33=-28/295, 9-48=-398/95, 35-48=-314/93, 8-49=-257/71, 40-51=-255/105, 13-56=-317/83, 31-56=-383/97

NOTES

WEBS

FORCES

BOT CHORD

Unbalanced roof live loads have been considered for this design. 1)

- Wind: ASCE 7-10; Vult=140mph (3-second gust) Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C 2) Exterior (2) -1-0-0 to 3-0-6, Interior (1) 3-0-6 to 20-0-10, Exterior (2) 20-0-10 to 24-2-0, Interior (1) 24-2-0 to 41-4-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult 3) qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pf=35.0 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; 4) Partially Exp.; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 35.0 psf on overhangs non-concurrent with other live loads. 6)
- All plates are MT20 plates unless otherwise indicated.

Page: 1

Continued on page 2


Job Truss Type Qty 105 Castle Rd Truss [PRELIM] Q15203 A03GE Common Structural Gable Job Reference (optional) 8.630 s May 25 2023 MiTek Industries, Inc. Mon Mar 11 21:44:05 2024 Page 1 ID:ke0fYXirtP0cpvWCSYBSm12YR8x-iiwTR?rtd4zAlLmU4ZMvJBh7rwxBfcOMz7fSCRzbtk8 13-6-8 20-2-0 6-11-0 15-3-12 26-9-8 33-5-0 40-4-0 41-4-0 1-0-0 4-10-4

Repair to Shorten Truss 1-9-0

Scale = 1:74.8 5x6 =

Add 2x4 #2 SPF As Shown

5.50 12



[2:0-0-15,0-2-0], [6:0-2-0,0-1-8], [11:0-1-0,0-2-4], [13:0-1-12,0-2-0], [14:0-1-8,0-1-8], [16:0-3-12,0-1-8], [17:0-1-8,0-1-8], [19:0-2-4,0-1-8], [21:0-2-12,0-2-0],Plate Offsets (X,Y)--[26:0-2-4,0-2-0]

| TCLL (roof) Snow (Pf) TCDL | 30.0 35.0 15.0 | Plate Grip DOL 1.15 Lumber DOL 1.15 Rep Stress Incr YES | TC 0.84 BC 0.88 WB 0.55 | Vert(LL) -0.32 14-16 >932 360 Vert(CT) -0.50 14-16 >593 240 Horz(CT) 0.04 13 n/a n/a | MT20 197/144 |
|----------------------------------|----------------------|---|-------------------------------|--|-------------------------|
| BCLL BCDL | 0.0 * 10.0 | Code IRC2015/TPI2014 | Matrix-MSH | Horz(CT) 0.04 13 n/a n/a | Weight: 294 lb FT = 20% |

LUMBER-BRACING-

TOP CHORD 2x4 SPF 1650F 1.5E *Except*

T1: 2x4 SPF No.2 **BOT CHORD** 2x4 SPF No.2

WEBS 2x4 SPF No.2 *Except* W1: 2x6 SPF 1650F 1.5E

OTHERS 2x4 SPF No.2

LOADING (psf)

TOP CHORD

BOT CHORD

WEBS

Rigid ceiling directly applied or 6-0-0 oc bracing, Except:

10-0-0 oc bracing: 14-16,13-14.

7-16, 8-16, 10-13, 6-17 1 Row at midpt

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

Structural wood sheathing directly applied or 3-10-14 oc purlins, except

REACTIONS. All bearings 15-5-8 except (jt=length) 13=0-5-8.

Max Horz 26=-158(LC 17) (lb) -

Max Uplift All uplift 100 lb or less at joint(s) 18 except 26=-112(LC 16),

13=-243(LC 17), 21=-245(LC 16), 17=-269(LC 17)

Max Grav All reactions 250 lb or less at joint(s) 18, 20, 22, 23, 24, 25 except 26=535(LC 23), 13=1532(LC 24), 21=657(LC 23), 17=2365(LC 1), 17=2365(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown

TOP CHORD 2-65=-442/193, 3-4=-34/374, 4-5=-12/509, 5-6=0/539, 6-66=-465/205, 7-66=-330/226,

7-67=-383/209, 8-67=-608/188, 8-9=-1519/318, 9-10=-1772/301, 10-68=-592/205,

11-68=-736/186, 2-26=-569/266, 11-13=-715/259

BOT CHORD 20-21=-406/237, 19-20=-406/237, 18-19=-406/237, 17-18=-406/237, 17-69=-510/265,

16-69=-510/265, 16-70=-37/1239, 15-70=-37/1239, 15-71=-37/1239, 14-71=-37/1239,

13-14=-228/1790

WEBS 7-16=-279/14, 8-16=-1286/334, 8-14=-59/642, 10-14=-479/248, 10-13=-1446/154,

3-21=-676/297, 5-17=-499/154, 6-17=-1808/192, 6-16=-132/1611

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -1-0-0 to 3-0-6, Interior(1) 3-0-6 to 20-2-0, Exterior(2) 20-2-0 to 24-2-6, Interior(1) 24-2-6 to 41-4-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pf=35.0 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 5) Unbalanced snow loads have been considered for this design.
- 6) This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 35.0 psf on overhangs non-concurrent with other live loads.
- 7) All plates are 1.5x4 MT20 unless otherwise indicated.
- 8) Gable studs spaced at 2-0-0 oc.
- 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Continued on page 2





Run: 8.53 S Jan 25 2022 Print: 8.530 S May 4 2022 MiTek Industries, Inc. Thu Jul 21 14:52:54

Structural wood sheathing directly applied or 6-0-0 oc purlins.

installed during truss erection, in accordance with Stabilizer

6-16 MiTek recommends that Stabilizers and required cross bracing be

Rigid ceiling directly applied or 10-0-0 oc bracing.

1 Row at midpt

Installation guide.




Plate Offsets (X, Y): [13:0-2-8,0-3-0]

| Loading | (psf) | Spacing | 2-0-0 | CSI | | DEFL | in | (loc) | l/defl | L/d | PLATES | GRIP |
|-------------|-------|-----------------|-----------------|------------|------|-----------|------|-------|--------|-----|---------------|----------|
| TCLL (roof) | 30.0 | Plate Grip DOL | 1.15 | TC | 0.07 | Vert(LL) | n/a | - | n/a | 999 | MT20 | 197/144 |
| Snow (Pf) | 35.0 | Lumber DOL | 1.15 | BC | 0.05 | Vert(TL) | n/a | - | n/a | 999 | | |
| TCDL | 15.0 | Rep Stress Incr | YES | WB | 0.18 | Horiz(TL) | 0.01 | 11 | n/a | n/a | | |
| BCLL | 0.0* | Code | IRC2015/TPI2014 | Matrix-MSH | | | | | | | | |
| BCDL | 10.0 | [| | | | | | | | | Weight: 98 lb | FT = 20% |

BRACING

WEBS

TOP CHORD

BOT CHORD

LUMBER

TOP CHORD 2x4 SPF No.2 **BOT CHORD** 2x4 SPF No.2 OTHERS 2x4 SPF No.2

REACTIONS All bearings 19-8-15.

(lb) - Max Horiz 1=254 (LC 11)

Max Uplift All uplift 100 (lb) or less at joint(s) 1, 11, 20 except 12=-112 (LC 15), 13=-114 (LC 15), 14=-121 (LC 15), 15=-115 (LC 15), 17=-118 (LC 14), 18=-118 (LC 14), 19=-125 (LC 14)

Max Grav All reactions 250 (lb) or less at joint(s) 1, 11, 12, 13, 14, 18, 19 except 15=261 (LC 22), 16=251 (LC 24), 17=263 (LC 21), 20=267 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 1-2=-296/209, 10-11=-251/168

NOTES

Unbalanced roof live loads have been considered for this design.


- Wind: ASCE 7-10; Vult=140mph (3-second gust) Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C 2) Exterior (2) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 9-10-12, Exterior (2) 9-10-12 to 12-10-12, Interior (1) 12-10-12 to 19-5-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pf=35.0 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; 3) Partially Exp.; Ct=1.10
- All plates are 1.5x4 MT20 unless otherwise indicated. 4)
- Gable requires continuous bottom chord bearing. 5)
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads. 6)
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 11, 20 except (jt=lb) 17=117, 18=118, 19=125, 15=114, 14=121, 13=113, 12=111.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



Repair to Shorten Truss 1-9-0; Trusses V01GE, V02, V03, V04, V05, V17, V18, V19GE

4x4 = Scale = 1:55.9



| 0-0-6 26-9-3 | |
|---|--|
| Code Code | ES GRIP 197/144 t: 127 lb FT = 20% |

26-9-8

LUMBER-

TOP CHORD 2x4 SPF No.2 BOT CHORD 2x4 SPF No.2 OTHERS 2x4 SPF No.2 BRACING-

BOT CHORD WEBS Structural wood sheathing directly applied or 6-0-0 oc purlins. Rigid ceiling directly applied or 10-0-0 oc bracing.

1 Row at midpt 7-20

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 26-9-8.

(lb) - Max Horz 1=-252(LC 10)

Max Uplift All uplift 100 lb or less at joint(s) 1, 21, 22, 23, 24, 19, 17, 16, 15 except 25=-126(LC 14),

14=-124(LC 15)

Max Grav All reactions 250 lb or less at joint(s) 1, 13, 22, 24, 17, 15 except 20=257(LC 24), 21=254(LC 21), 23=252(LC 21), 25=366(LC 21), 19=251(LC 22), 16=251(LC 22), 14=359(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-25=-280/144, 12-14=-275/142

NOTES-

1) Unbalanced roof live loads have been considered for this design.

- 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) 0-5-11 to 3-5-2, Interior(1) 3-5-2 to 13-5-2, Exterior(2) 13-5-2 to 16-5-2, Interior(1) 16-5-2 to 26-3-14 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pf=35.0 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
- 4) All plates are 1x4 MT20 unless otherwise indicated.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 21, 22, 23, 24, 19, 17, 16, 15 except (jt=lb) 25=126, 14=124.

9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



03/12/2024 4 of 4

